

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

RECEIVED  
DEC 28 1992

2. Name of Operator  
Meridian Oil Inc.

OIL CON. DIV  
DIST. C

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
900'FNL, 1210'FEL Sec.26 T-28-N, R-6-W, NMPM

5. Lease Number  
SF-079050A  
6. If Indian, All. or  
Tribe Name  
7. Unit Agreement Name  
San Juan 28-6 Unit  
8. Well Name & Number  
San Juan 28-6 U #434  
9. API Well No.  
30-039-25239  
10. Field and Pool  
Basin Frt Coal  
11. County and State  
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

12-05-92 Spudded well at 11:00 pm. Drilled to 220'. Ran 5 jts. 8 5/8", 24.0#, K-55 surface casing set at 214'. Cemented with 235 sks. Class "B" with 3% calcium chloride and 1/4#/sx flocele (277 cu.ft.) circulated to surface. WOC 12 hrs. Tested 600#/30 min., ok.

12-10-92 TD 3450'. Ran 84 jts. 4 1/2", 10.5#, K-55 casing, 3436' set @ 3448'. Float collar set @ 3403'. Stage tool @ 2864'. Cemented first stage with 115 sks. Class "B" 65/35 Pozmix, 6% gel, 5#/sx gilsonite, 1/4#/sx cello-seal and 2% calcium chloride, (204 cu.ft.), tailed w/80 sx Class "B" w/2% calcium chloride (94 cu.ft.). Cemented 2nd stage with 600 sks. Class "B" 65/35 Pozmix, 6% gel, 2% calcium chloride, 5#/sx gilsonite, and 1/4#/sx cello-seal (1062 cu.ft.), tailed w/100 sx Class "B" w/2% calcium chloride (118 cu.ft.). WOC 18 hours. Circ 75 bbl. to surface.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 12/11/92

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

NMOCD

SWM