

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals.

RECEIVED
JUL 18 1994

OIL CON. DIV.
DIST. 3

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

AMOCO PRODUCTION COMPANY

Attention:

Julie Acevedo

3. Address and Telephone No.

P.O. Box 800 Denver, Colorado 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1080 FNL 560 FWL

Section 27 Township 28N Range 7W

5. Lease Designation and Serial No.

SF-078498

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

San Juan 28-7 Unit #135 M

9. API Well No.

30-039-25408

10. Field and Pool, or Exploratory Area Basin
Blanco Mesaverde/ Dakota

11. County or Parish, State

Rio Arriba, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment Notice	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other Spud & Set
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut-Off
	☐ Conversion to Injection
	☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud a 14.75" surface hole on 6/4/94 at 03:00 hrs. Drilled to 426'.

Set 11.75" 47# J-55 surface casing at 426'. Cemented with

300 sx CL B Circulated 20 BBLS to the surface.

Pressure tested casing to 2,000 psi. Drilled a 10.625" hole to a depth of

3025' on 6/12/94. Set 8.625" 32# J-55 Intermediate

casing at 3025' Cemented with 225 sx C1 A, 2nd stg 450 sx C1 B, tail 100 sx C1 B, DV @ 2450'

Circulated 25 BBLS to the surface. Pressure tested casing to 1,000 psi.

Drilled a 7.875" hole to a depth of 7267' on 6/15/94. Set 5.5" N-80 17# Production

casing at 7267'. Cemented with Lead 665 sx C1 A, tail 200 sx C1 G.

Rig released at 10:00 hrs. on 6/15/94.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Date

(This space for Federal or State office use)

JUL 18 1994

Approved by

Title

Conditions of approval, if any:

JUL 18 1994