## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993
LEASE DESIGNATION AND SERIAL NO.

		SF	
	SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
	Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		
	Use "APPLICATION FOR PERMIT-" for such proposals	Ą	
	SUBMIT IN TRIPLICATE	7. IF UNIT OR CA, AGREEMENT DESIGNATION	
1.	TYPE OF WELL	8. WELL NAME AND NO.	
	OIL WELL GAS WELL OTHER	SAN JUAN 28-7 UNIT #222M	
2.	NAME OF OPERATOR	9. API WELL NO.	
	CONOCO INC.	30-039-25562	
3.	ADDRESS AND TELEPHONE NO.	10. FIELD AND POOL, OR EXPLORATORY AREA	
	10 DESTA DR., SUITE 100W, MIDLAND, TX 79705-4500 (915) 686-5424	BASIN DAKOTA / BLANCO MV	
4.	LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Description)	11. COUNTY OR PARISH, STATE	
	916' FNL & 813' FWL, SEC. 25, T28N, R7W, UNIT LTR K	RIO ARRIBA, NM	
12.	CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
	TYPE OF SUBMISSION TYPE OF ACTION		
	□ Notice of Intern	Change of Plans	
	Recompletion	New Construction	
	Subsequent Recompletion  Plugging Back	Non-Routine Fracturing	
	Final Abandonment Notice Casing Repair	Water Shut-Off	
	(O) ↓ ↓ (C) ○ ○ □ Altering Casing	Conversion to Injection	
	DISTO B Other: Spud and Cement Report	Dispose Water	
<u> </u>		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)	
13.	Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)		
	and statistically difficult to this work.)		
	4-29-97 - Spudded Well. Drilled surface hole.		
	5-1-97 - Ran 6 joints 9-5/8", 36# K-55, St &C, R-3 casing. Landed at 289'. Cement with 165 sxs Clas B cement with 3%		
	CaCL2 and 1/4#/sk Cello Flake. WOC 12 hours. Pressure tested BOP's and 9-5/8" csg to 1500# and BOP's to		
	3000# high, 250# low. Tested okay. ND GRH add spacer, spool and NU same equipment. RI HiTag Cement		
	240 and drill cmt baffle plate @241 cmt and shoe @ 289'.		
	5-5-97 - Ran 81 jnts 7", 23# K-55, Lt&C, 8rd, R-3 Casing, landed @ 3614'. Cer	ment with380 sxs - Class B with 8%	
	Gz, 2% CACI2, 1/4#/sk Cello Flake. WOC 12 hours. Pressure tested BOP's to 3000#, okay. RIH Tag cement w/ 3-1/2" drill pipe @ 3517'. Drill cement anf float collar @ 3570'. Cmt shoe @3614' wash to btm.		
	5-11-97 - Ran 178 jnts 4-1/2", 1160#/10.50#, K-55, LT&C ST&C, 8rd, casing. Landed @7759'. Cement with 405 sxs		
	Class B, with 4 %gel, 2% Hcl, 6-1/4#/sk Gilsonite, 1/4#/sk Cello Flake. WOC. Nipple down BOP's and set 4-1/2" csg slips with casing wt 10	O 000# on honger make rough out	
	and install fuzz cap release rig.	0,000# On hangar make rough cut	
	· 경식 () ()		
14.	I hereby certify that the foregoing is true and correct		
	DEBRA BEMENDERF		
<u></u>		O INACCERNAL DE CORD	
	(This space for Federal or State office use)	11111 0 - 4007	
1	APPROVED BY TITLE	JHN 23 1997	
<u></u>	Conditions of approval, if any:	TICE	
	· · · · · · · · · · · · · · · · · · ·	FARMINGTON DISTRICT OFFICE	
		RY ILV	