

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(See other in-
structions on
reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other _____				5. LEASE DESIGNATION AND SERIAL NO. SF-079050B	
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other _____				7. UNIT AGREEMENT NAME San Juan 28-6 Unit	
2. NAME OF OPERATOR BURLINGTON RESOURCES OIL & GAS COMPANY				8. FARM OR LEASE NAME, WELL NO. San Juan 28-6 U #113M	
3. ADDRESS AND TELEPHONE NO. PO BOX 4289, Farmington, NM 87499 (505) 326-9700				9. API WELL NO. 30-039-25653	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 1190'FNL, 1730'FWL At top prod. interval reported below At total depth DHC-1521				10. FIELD AND POOL, OR WILDCAT Blanco MV/Basin DK	
11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA C Sec. 26, T-28-N, R-6-W				12. COUNTY OR PARISH Rio Arriba	
13. STATE New Mexico				14. PERMIT NO. DATE ISSUED	
15. DATE SPUNDED 3-15-97		16. DATE T.D. REACHED 3-22-97		17. DATE COMPL. (Ready to prod.) 4-20-97	
18. ELEVATIONS (DF, RKB, RT, BR, ETC.)* 6571 GR, 6583 KB		19. ELEV. CASINGHEAD		20. TOTAL DEPTH, MD & TVD 7860	
21. PLUG, BACK T.D., MD & TVD CIBP @ 6045		22. IF MULTIPLE COMPL., HOW MANY*		23. INTERVALS DRILLED BY 0-7860	
24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* 4938-5961 Mesaverde				25. WAS DIRECTIONAL SURVEY MADE	
26. TYPE ELECTRIC AND OTHER LOGS RUN CNL, CBL-CCL-GR				27. WAS WELL CORED No	
28. CASING RECORD (Report all strings set in well)					
CASING SIZE/GRADE		WEIGHT, LB./FT.		DEPTH SET (MD)	
9 5/8		36#		243	
7		20#		3602	
29. LINER RECORD					
SIZE		TOP (MD)		BOTTOM (MD)	
4 1/2		2864		7857	
30. TUBING RECORD					
SIZE		DEPTH SET (MD)		PACKER SET (MD)	
2 3/8		5925		CIBP @ 6045	
31. PERFORATION RECORD (Interval, size and number)					
4938, 4973, 5012, 5045, 5052, 5067, 5077, 5105, 5126					
5134, 5146, 5158, 5167, 5182, 5186, 5192, 5201, 5205,					
5236, 5260, 5274, 5286, 5306, 5332, 5464, 5478, 5519,					
5546, 5564, 5576, 5589, 5603, 5618, 5630, 5645, 5654,					
5672, 5696, 5746, 5786, 5808, 5825, 5886, 5904, 5918, 5961					
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.					
DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED			
4938-5332		2568 bbl sik wtr, 4000# 40/70 sd, 90,000# 20/40 sd			
5464-5961		2107 bbl sik wtr, 3149# 40/70 sd, 89,851# 20/40 sd			
33. PRODUCTION					
DATE FIRST PRODUCTION 4-20-97		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing			WELL STATUS (Producing or shut-in) SI
DATE OF TEST 4-20-97		HOURS TESTED		CHOKE SIZE	
FLOW. TUBING PRESS. SI 725		CASING PRESSURE SI 725		CALCULATED 24-HOUR RATE	
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold		TEST WITNESSED BY			
35. LIST OF ATTACHMENTS None					
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records					

SIGNED Nancy Ottmann TITLE Regulatory Administrator

DATE 5-13-97

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

BY

ACCEPTED FOR RECORD

MAY 16 1997

FARMINGTON DISTRICT OFFICE

27. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	2690'	2770'	White, cr-gr ss.	Ojo Alamo	2690'	
Kirtland	2770'	3028'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	2770'	
Fruitland	3028'	3369'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	3028'	
Pictured Cliffs	3369'	3540'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	3369'	
Lewis	3540'	3970'	Shale w/siltstone stringers	Lewis	3540'	
Huerfanito Bentonite*	3970'	4330'	White, waxy chalky bentonite	Huerfanito Bent.	3970'	
Chacra	4330'	4935'	Gry fn grn silty, glauconitic sd stone w/drk gry shale	Chacra	4330'	
Cliff House	4935'	5207'	ss. Gry, fine-grn, dense sil ss.	Cliff House	4935'	
Menefee	5207'	5552'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	5207'	
Point Lookout	5552'	5665'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Pt.Lookout	5552'	
Mancos	5665'	6813'	Dark gry carb sh.	Mancos	5665'	
Gallup	6813'	7502'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg.interbed sh	Gallup	6813'	
Greenhorn	7502'	7608'	Highly calc gry sh w/thin lmst.	Greenhorn	7502'	
Graneros	7608'	7718'	Dk gry shale, fossil & carb w/pyrite incl.	Graneros	7608'	
Dakota	7718'	7860'	Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks	Dakota	7718'	

38. GEOLOGIC MARKERS

*Huerfanito Bentonite is the legal top of Mesa Verde in New Mexico (North of the Chacra line)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH

38.

GEOLOGIC MARKERS

Ojo Alamo	2690'	2770'	White, cr-gr ss.			
Kirtland	2770'	3028'	Gry sh interbedded w/tight, gry, fine-gr ss.			
Fruitland	3028'	3369'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Ojo Alamo	2690'	
Pictured Cliffs	3369'	3540'	Bn-Gry, fine grn, tight ss.	Kirtland	2770'	
Lewis	3540'	3970'	Shale w/siltstone stringers	Fruitland	3028'	
Huerfanito Bentonite*	3970'	4330'	White, waxy chalky bentonite	Pic.Cliffs	3369'	
Chacra	4330'	4935'	Gry fn grn silty, glauconitic sd stone w/dk gry shale	Lewis	3540'	
Cliff House	4935'	5207'	ss. Gry, fine-grn, dense sil ss.	Huerfanito Bent.	3970'	
Menefee	5207'	5552'	Med-dark gry, fine gr ss, carb sh & coal	Chacra	4330'	
Point Lookout	5552'	5665'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Cliff House	4935'	
Mancos	5665'	6813'	Dark gry carb sh.	Menefee	5207'	
Gallup	6813'	7502'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg. interbed sh	Pt.Lookout	5552'	
Greenhorn	7502'	7608'	Highly calc gry sh w/thin lmst.	Mancos	5665'	
Graneros	7608'	7718'	Dk gry shale, fossil & carb w/pyrite incl.	Gallup	6813'	
Dakota	7718'	7860'	Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks	Greenhorn	7502'	
				Graneros	7608'	
				Dakota	7718'	

*Huerfanito Bentonite is the legal top of Mesa Verde in New Mexico (North of the Chacra line)