UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	5.	Lease Number NMSF-079522
Type of Well GAS	6.	If Indian, All. or Tribe Name
MAY 2002	7.	Unit Agreement Name
Name of Operator		
BURLINGTON RESOURCES OIL & GAS COMPANY		San Juan 28-5 Unit
	8.	Well Name & Number San Juan 28-5 U #7:
Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No. 30-039-26308
. Location of Well, Footage, Sec., T, R, M	10.	Field and Pool Blanco MV/Basin DK
2270'FNL, 2530'FEL, Sec.34, T-28-N, R-5-W, NMPM	11.	County and State Rio Arriba Co, NM
DHC-683az		
2. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, Type of Submission Type of Action		
Notice of Intent Abandonment Change	of Pl	ans tion
Plugging Back Non-Rou	utine	Fracturing
Casing Repair Water S	Shut o	ff o Injection
Final Abandonment Altering Casing Convers X Other - Spud	51011 0	0 111,000_0
3. Describe Proposed or Completed Operations	9'. Ci	rc hole clean.
3. Describe Proposed or Completed Operations 4-26-02 MIRU. Spud well @ 5:15 p.m. 4-26-02. Drill to 22 TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, switch with the second w	t w/2% bl cmt	calcium chloride to surface. WOC.
4-26-02 MIRU. Spud well @ 5:15 p.m. 4-26-02. Drill to 22 TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, 8 wtr ahead. Cmtd w/104 sx Class "G" Type III cmt	t w/2% bl cmt	calcium chloride to surface. WOC.
4-26-02 MIRU. Spud well @ 5:15 p.m. 4-26-02. Drill to 22 TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, 8 wtr ahead. Cmtd w/104 sx Class "G" Type III cmt	t w/2% bl cmt	calcium chloride to surface. WOC.
4-26-02 MIRU. Spud well @ 5:15 p.m. 4-26-02. Drill to 22 TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, 8 wtr ahead. Cmtd w/104 sx Class "G" Type III cmt	t w/2% bl cmt	calcium chloride to surface. WOC.
4-26-02 MIRU. Spud well @ 5:15 p.m. 4-26-02. Drill to 22 TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, 8 wtr ahead. Cmtd w/104 sx Class "G" Type III cmt	t w/2% bl cmt	calcium chloride to surface. WOC.
4-26-02 MIRU. Spud well @ 5:15 p.m. 4-26-02. Drill to 22 TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, 8 wtr ahead. Cmtd w/104 sx Class "G" Type III cmt	t w/2% bl cmt	calcium chloride to surface. WOC.
4-26-02 MIRU. Spud well @ 5:15 p.m. 4-26-02. Drill to 22 TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, s wtr ahead. Cmtd w/104 sx Class "G" Type III cm (147 cu.ft.). Displace w/14 bbl wtr. Circ 17 bl 4-27-02 NU BOP. PT BOP & csg to 600 psi/30 min, OK. Dril	t w/2% bl cmt	calcium chloride to surface. WOC.
4-26-02 MIRU. Spud well @ 5:15 p.m. 4-26-02. Drill to 22 TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, 8 wtr ahead. Cmtd w/104 sx Class "G" Type III cmt	t w/2% bl cmt	calcium chloride to surface. WOC.
4-26-02 MIRU. Spud well @ 5:15 p.m. 4-26-02. Drill to 22 TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, s wtr ahead. Cmtd w/104 sx Class "G" Type III cm (147 cu.ft.). Displace w/14 bbl wtr. Circ 17 bl 4-27-02 NU BOP. PT BOP & csg to 600 psi/30 min, OK. Dril	t w/2% bl cmt	calcium chloride to surface. WOC.
4-26-02 MIRU. Spud well @ 5:15 p.m. 4-26-02. Drill to 22 TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, s wtr ahead. Cmtd w/104 sx Class "G" Type III cm (147 cu.ft.). Displace w/14 bbl wtr. Circ 17 bl 4-27-02 NU BOP. PT BOP & csg to 600 psi/30 min, OK. Dril	t w/2% bl cmt	calcium chloride to surface. WOC.
4-26-02 MIRU. Spud well @ 5:15 p.m. 4-26-02. Drill to 22 TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, swtr ahead. Cmtd w/104 sx Class "G" Type III cm (147 cu.ft.). Displace w/14 bbl wtr. Circ 17 bl 4-27-02 NU BOP. PT BOP & csg to 600 psi/30 min, OK. Dril APD ROW related	t w/2% bl cmt	calcium chloride to surface. WOC.
APD ROW related APD Row related APD Row related APD Row related To hereby certify that the foregoing is true and correct. Title Pegulatory Supervisor	t w/2% bl cmt ling a	calcium chloride to surface. WOC. whead.
4-26-02 MIRU. Spud well @ 5:15 p.m. 4-26-02. Drill to 22 TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, wtr ahead. Cmtd w/104 sx Class "G" Type III cm (147 cu.ft.). Displace w/14 bbl wtr. Circ 17 bl 4-27-02 NU BOP. PT BOP & csg to 600 psi/30 min, OK. Dril APD ROW related 14. I hereby certify that the foregoing is true and correct.	t w/2% bl cmt ling a	calcium chloride to surface. WOC. shead.