(SUBMIT IN TRIPLICATE)

Land Office Santa Fe

UNITED STATES

Lease No. 077973 Unit E. H. Netten

GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS	
NOTICE OF INTENTION TO DRILL	THE TOTAL PROPERTY OF THE PROP
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO PULL OR ALTER CASING	TODOLOGINI REPORT OF ARANDONALTAR
NOTICE OF INTENTION TO ABANDON WELL.	SUPPLEMENTARY WELL HISTORY
TOTAL DOM WELL	IN 3
(INDICATE ANALYS	MAT
WILLIAM STATE BY CHECK I	MARK NATURE OF REPORT, NOTICE, OR OTHER DATE:
	Parmington, New Mexico Nay 30 , 19 56
(1/4 Sec. and Sec. No.)	rom $\begin{cases} \frac{NL}{S} \text{ line and } \frac{660}{660} \text{ ft. from } \frac{E}{W} \text{ line of sec.} \end{cases}$
Wildcat (Twp.)	(Range) (Meridian)
(Field)	Juan
	nty or Subdivision) (State or Territory)
e elevation of the derrick floor above sea	land: 4350
brokes to bing the above well:	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ill other important proposed work) in the following manner:
1) Set 60 sack cement plug from 2) Set 60 sack cement plug from 3) Set 60 sack cement plug from 4) Set 70 sack cement plug from 5) Set 50 sack cement plug from 6) Set 10 sack cement plug at a 7) Hole filled with med beauty	in the following manner: m 5900 to 5738 feet. m 4150 to 3988 feet. m 2150 to 1988 feet. m 1400 to 1215 feet. bottom of surface pipe, 525 feet. marface and erect 4-foot pipe market
1) Set 60 sack cement plug from 2) Set 60 sack cement plug from 3) Set 60 sack cement plug from 4) Set 70 sack cement plug from 5) Set 50 sack cement plug at 6 6) Set 10 sack cement plug at 6 6) Set 10 sack cement plug at 6 7) Hole filled with mad between 8) Restore ground to original c	in the following manner: m 5900 to 5738 feet. m 4150 to 3988 feet. m 2150 to 1988 feet. m 1400 to 1215 feet. bottom of surface pipe, 525 feet. murface and erect 4-foot pipe marker. i plugs. contour.
1) Set 60 sack cement plug from 2) Set 60 sack cement plug from 3) Set 60 sack cement plug from 4) Set 70 sack cement plug from 5) Set 50 sack cement plug from 6) Set 10 sack cement plug at h 6) Set 10 sack cement plug at h 7) Hole filled with mad between 8) Restore ground to original company STANCIND CH & GAS C	in the following manner: m 5900 to 5738 feet. m 4150 to 3968 feet. m 2150 to 1968 feet. m 1400 to 1215 feet. bottom of surface pipe, 525 feet. mrface and erect 4-foot pipe marker.
1) Set 60 sack coment plug from 2) Set 60 sack coment plug from 3) Set 60 sack coment plug from 4) Set 70 sack coment plug from 5) Set 50 sack coment plug from 6) Set 10 sack coment plug at a 6) Set 10 sack coment plug at a 7) Hole filled with mad between 8) Restore ground to original comerstand that this plan of work must receive approval in pany STANCIAN CH & GAS Coment P. 0. 10% 487	in the following manner: m 5900 to 5738 feet. m 4150 to 3968 feet. m 2150 to 1968 feet. m 1400 to 1215 feet. bottom of surface pipe, 525 feet. mrface and erect 4-foot pipe marker.
1) Set 60 sack coment plug from 2) Set 60 sack coment plug from 3) Set 60 sack coment plug from 4) Set 70 sack coment plug from 5) Set 50 sack coment plug from 6) Set 10 sack coment plug at a 6) Set 10 sack coment plug at a 7) Hole filled with mad between 8) Restore ground to original comerstand that this plan of work must receive approval in pany STANCIAN CH & GAS Coment P. 0. 10% 487	in the following manner: 2500 to 5738 feet. 2150 to 3988 feet. 2150 to 1988 feet. 2150 to 1215 feet. 2500 to 3988 feet. 2600 to 1215 feet. 2500 to 3988 feet. 2600 to 1215 feet. 2600 t
1) Set 60 sack cement plug from 2) Set 60 sack cement plug from 3) Set 60 sack cement plug from 4.) Set 70 sack cement plug from 5) Set 50 sack cement plug from 6) Set 10 sack cement plug at h 6) Set 10 sack cement plug at h 7) Hole filled with mad between 8) Restore ground to original company STANCIND CH & GAS C	in the following manner: 2500 to 5738 feet. 2150 to 3988 feet. 2150 to 1988 feet. 2150 to 1215 feet. 2500 to 3988 feet. 2600 to 1215 feet. 2500 to 3988 feet. 2600 to 1215 feet. 2600 t
1) Set 60 sack coment plug from 2) Set 60 sack coment plug from 3) Set 60 sack coment plug from 4) Set 70 sack coment plug from 5) Set 50 sack coment plug from 6) Set 10 sack coment plug at a 6) Set 10 sack coment plug at a 7) Hole filled with mad between 8) Restore ground to original comerstand that this plan of work must receive approval in pany STANCIAN CH & GAS Coment P. 0. 10% 487	in the following manner: 2500 to 5738 feet. 2150 to 3988 feet. 2150 to 1988 feet. 2150 to 1215 feet. 2500 to 3988 feet. 2600 to 1215 feet. 2500 to 3988 feet. 2600 to 1215 feet. 2600 t
1) Set 60 sack coment plug from 2) Set 60 sack coment plug from 3) Set 60 sack coment plug from 4) Set 70 sack coment plug from 5) Set 50 sack coment plug from 6) Set 10 sack coment plug at a 6 set 10 sack coment plug at a 7) Hole filled with mad between 8) Restore ground to original coment plug at a feature ground to original composition of the same stand that this plan of work must receive approval in STANCIND CH & GAS Coment P. 0. 134 GAS Coment Plug from the same	in the following manner: 2500 to 5738 feet. 2150 to 3988 feet. 2150 to 1988 feet. 2150 t