

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1090' FSL, 1750' FWL, Sec. 26, T-27-N, R-9-W, NMPM

5. Lease Number
SF-080117

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

Huerfanito Unit

8. Well Name & Number
Huerfanito Unit #85

9. API Well No.
30-045-06209

10. Field and Pool
Blanco MV/Basin DK

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action	
☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

11-29-95 MIRU. SDON.
11-30-95 ND WH. NU BOP. TOO H w/1 1/4" tbg. SDON.
12-5-95 TOO H w/212 jts tbg. TIH to 6738'. Plug #1: pump 44 sx Class "B" cmt down csg @ 6500-6738'. Displaced w/24.5 bbl wtr to 5733'. TOO H. SDON.
12-6-95 TIH, tag TOC @ 6082'. (Verbal approval to change plans from Wayne Townsend, BLM). Plug #2: pump 17 sx Class "B" cmt down tbg @ 5633-5733'. Displace w/21 bbl wtr. POOH. TIH w/5 1/2" gauge ring to 4500'. TOO H. TIH w/5 1/2" CIBP, set @ 4480'. TOO H. Load hole w/60 bbl wtr. PT csg & CIBP to 500 psi, OK. TIH, tag CIBP. Plug #3: pump 6 sx Class "B" cmt on top of CIBP to 4430'. Displace w/15.5 bbl wtr. TOO H to 3825'. Plug #4: pump 17 sx Class "B" cmt @ 3725-3825'. Displace to 3725' w/14 bbl wtr. POOH to 2250'. Plug #5: pump 38 sx Class "B" cmt @ 1960-2243'. Displace w/7.25 bbl wtr to 1960'. TOO H. TIH, perf 4 sqz holes @ 1478'. TOO H. Load hole w/wtr. Establish injection. SDON.
12-7-95 TIH w/5 1/2" cmt retainer, set @ 1262'. Plug #6: pump 102 sx Class "B" cmt below cmt retainer, pump 12 sx Class "B" cmt above cmt retainer. TOO H. TIH, perf 2 sqz holes @ 393'. TOO H. Establish circ down csg & out bradenhead. Plug #7: pump 156 sx Class "B" cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. ND BOP. Cut off WH. Fill csg w/8 sx Class "B" cmt. Install dry hole marker w/10 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 12-7-95.

14. I hereby certify that the foregoing is true and correct.

Signed *Regina D. Stahpud* Title Regulatory Administrator Date 1/2/96

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any: _____

Date **APPROVED**

NMCCD

[Signature] JAN 1 1996