Form 9=3318 (Feb. 1951) --26-X.

"CCPY"

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

and Ofice Farnington						
ease	_{No.} Sa	nta	Гe	0780	<u>)</u> 92	
Unit	∃ovt	Cou	thi	t .		

.......

	SUNDRY NOTICES A	AND REPORTS ON WELL3
NOTICE OF INTI	ENTION TO DRILL ENTION TO CHANGE PLANS ENTION TO TEST WATER SHUT-OFF ENTION TO RE-DRILL OR REPAIR WELL ENTION TO SHOOT OR ACIDIZE ENTION TO PULL OR ALTER CASING	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASING. SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMEN SUPPLEMENTARY WELL HISTORY.
NOTICE OF INT	ENTION TO ABANDON WELL.	Froduction Casing
	(INDICATE ABOVE BY CHECK MA	RK NATURE OF REPORT, NOTICE, OR OTHER DATA
		June 29 , 1956
Go Well No	ovt Douthit 5 is located1650_ft.fro	om. $\begin{Bmatrix} \mathbf{X} \\ S \end{Bmatrix}$ line and 1650 ft. from $\begin{Bmatrix} \mathbf{K} \\ \mathbf{W} \end{Bmatrix}$ line of sec. 26
NE SW Sec	26 27 N	1]W NM DM (Range) (Meridian)
(½ Sec.		• • •
West Kutz	Field) (Coun	ounty New Mexico (State o Territory)
The elevation	on of the derrick floor above sea	level is 6432 ft. G.L.
1110 010 1		AILS OF WORK
(State names of		sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement ill other important proposed work)
with 75 S	Sax 2% Gel Cement. Casing zers. Pumped plug to 1965	, J-55 Casing landed at 2012! KB and Cementer equipped with Baker Shoe, Float Collar, and with 500 PSI. Float Held DK. Fan of cement behind casing at 1966! KB.
		al in writing by the Geological Survey before operations may be commenced.
Company .	The British-American Oi	Producing Co.
Address	Box 180	
	Denver, Colorado	By
	U. S. 60	OVERNMENT PRINTING OFFICE 16-8437-5

n de la composition La composition de la