

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 078092
Unit Prod. South 11

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	SURFACE Cased

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 7, 1951

Well No. 2 is located 1450' ft. from N line and 790 ft. from W line of sec. 2

14 54 Sec. 27 27E 11W 60N
(¼ Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Mont. Vista Canyon San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6330 ft. 10 feet.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled 12-1/4" hole to 242'. Ripped up and ran surface casing as follows:
1 - 8-5/8" guide shoe, Baker, Tanne Pattern 1.25
2 - Jts. 8-5/8" 24.0' 3-55 8-4 Tds. "H" casing 232.42
Total string 237.90
Landed at 238

Cemented with 210 sacks of Portland, 2% Calcium chloride. Pumped plug to 215'. Good cement returns to surface. Job completed 9:30 AM 3-7-51.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The British-American Oil Prod. Co.

Address P. O. Drawer 330

Permian, N.M.

By Don R. Stone

Title Field Superintendent