

COPY FOR  
STATE OF NEW MEXICO  
OIL CONSERVATION  
COMMISSION  
SUBMIT IN TRIPLICATE TO  
DISTRICT OFFICE

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 077951  
Unit Jack Frost



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	DIST. 3
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	1
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Farmington, New Mexico, January 18, 1952

Well No. 1-1 is located 1650 ft. from N line and 990 ft. from E line of sec. 26  
26 of Section 26 7-27-N 1-10-E R17N  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Falchor-Kata (Ext.) San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6257 ft. (C.I.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate casing joints, cementing, lining, and the rotary tools used. This tool rig moved on to location and well was cleaned out to bottom. Well was plugged back with pea gravel from 2151 to 2117 feet and shot with 318 qts. of SBC from 2057 to 2117 feet, with gravel cap from 2057 to 2052 feet and cal-seal cap from 2052 to 2012 feet. Shot was detonated at 6:14 P.M. on November 14, 1951. Well was cleaned out to 2117 feet. Well was shut in 3 hours. Shut in casing pressure, 225 psi. Well measured 240 MCF per day after one hour blow down through 2" casing outlet with pitot tube through 2" pipe nipple November 19, 1951. Well was then plugged back with pea gravel from 2117 to 2114 feet and was shot with 160 qts. SBC from 2055 to 2114 feet, with gravel cap from 2055 to 2050 feet and cal-seal cap from 2050 to 2009 feet. Shot was detonated at 6:15 A.M. on November 22, 1951. Well was cleaned out to bottom. 1 1/2" tubing was landed at 2110 feet. Well was shut in for 72 hours. Shut in casing pressure was 477 psi. Well measured 155 MCF per day after 3 hour blow down through 2" casing outlet with pitot tube through 2" pipe nipple December 22, 1951.

I understand that this plan of work must receive approval from the State before operations may be commenced.

Company Stanolind Oil and Gas Company  
Address Box 457  
Farmington, New Mexico  
By L. B. Spaw, Jr.  
Title Production Foreman