

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

RECEIVED
FEB 17 1995

2. Name of Operator

MERIDIAN OIL

OIL CON. DIV.
DIST. 3

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1345'FNL, 1575'FEL, Sec.27, T-27-N, R-9-W, NMPM

5. Lease Number
SF-078356B

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

Huerfanito Unit

8. Well Name & Number
Huerfanito Unit #47

9. API Well No.
30-045-06270

10. Field and Pool
Basin Fruitland Coal

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

2-2-95 MIRU. ND WH. NU BOP. TIH, tag @ 2168'. POOH to 2148'. Plug #1: pump 62 sx Class "B" cmt inside csg @ 1600-2148'. TOOH to 1465'. SDON.

2-3-95 Load hole w/20 bbl wtr. PT csg to 500 psi, OK. TIH, tag cmt plug @ 1608'. POOH to 1520'. Perf 4 sqz holes @ 1520'. POOH. Attempt to establish circ into perfs. (Verbal approval to change plans from Steve Mason, BLM). TOOH to 1370'. Perf 2 sqz holes @ 1370'. Establish injection. TIH w/5 1/2" cmt retainer to 1592'. Plug #2: pump 22 sx Class "B" cmt inside csg @ 1400-1592'. POOH to 1332', reverse circ well clean w/15 bbl wtr. Set cmt retainer @ 1332'. Establish injection. Plug #3: pump 33 sx Class "B" cmt below cmt retainer @ 1217-1332'. Spot 13 sx Class "B" cmt above cmt retainer to 1217'. TOOH. TIH, perf 2 sqz holes @ 155'. Establish circ out bradenhead w/8 bbl wtr. Plug #4: pump 59 sx Class "B" cmt down csg and out bradenhead. Circ 1 bbl cmt out bradenhead. WOC. ND BOP. Cut off WH. Found cmt down 30' in 5 1/2" csg and down 15' in annulus. Fill 5 1/2" csg and 5 1/2" x 8 5/8" annulus w/5 sx cmt. Install dry hole marker w/15 sx cmt. RD. Well plugged and abandoned 2-3-95.

14. I hereby certify that the foregoing is true and correct.

Signed *[Signature]* Title Regulatory Affairs Date 2/9/95

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

APPROVED

FEB 15 1995

DISTRICT MANAGER

WOCOD