4-086	6	
1-40		
1-0-	1.	_

4-03	35
1-110	
1-D.	1-4

X

Form 9-881 a (Feb. 1951)

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

	Bud App	lget l prova	Bures l exp	u N ires	o. 42 12-31	-R358 -60.	3.4.
Land O	ffice					 -	
Loase N	lo	Mi:	-05	65	64.		
Unit							
Campl	w l	1 1	l od	9 2	ai	*3	**
Completion				Ŋ	77	 	

NE/4 NE/4 Sec. 28 27 N 12 N NAPM (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian) Resin Pakerta Sen Juan New Mexico (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 5823 ft. GL DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereing points, and all other important proposed work) 24/62 T. D. 5930°. Ran 188 jts. 5962° of 4 1/2° 10.50% Lone Star casing second county of the collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 595						Car U V L• :
Well No. 1 is located T90 ft. from Nay 28 19 Well No. 1 is located T90 ft. from Nay 28 19 Well No. 2 is located T90 ft. from Nay 28 19 Well No. 3 is located T90 ft. from Nay 28 19 Well No. 4 is located T90 ft. from Nay 28 19 Well No. 5 is located T90 ft. from Nay 28 19 Well No. 6 is located T90 ft. from Nay 28 19 Well No. 7 is located T90 ft. from Nay 28 19 Well No. 8 is located T90 ft. from Nay 28 19 Well No. 9 is located T90 ft. from Nay 28 19 Well No. 1 is located T90 ft. from Nay 28 19 Well No. 1 is located T90 ft. from Nay 28 19 Well No. 1 is located T90 ft. from Nay 28 19 Well No. 2 is located T90 ft. from Nay 28 19 Well No. 3 is located T90 ft. from Nay 28 19 Well No. 1 is located T90 ft. from Nay 28 19 Well No. 2 is located T90 ft. from Nay 28 19 Well No. 3 is located T90 ft. from Nay 28 19 Well No. 4 is located T90 ft. from Nay 28 19 Well No. 1 is located T90 ft. from Nay 28 19 Well No. 2 is located T90 ft. from Nay 28 19 Well No. 3 is located T90 ft. from Nay 28 19 Well No. 4 is located T90 ft. from Nay 28 19 Well No. 1 is located	SUNDRY N	OTICES A	ND REPO	ORTS ON	WELLS	29 1962
Well No. 1 is located 790 ft. from No. line and 790 ft. from E line of sec. 2. NE/4 NE/4 Sec. 23 27 N 12 9 NAPM (6 Sec. and Sec. No.) (Twp.) (Range) (Meridian) New Mexico (Field) (Country or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 5823 ft. Gt. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, certain points, and all other important proposed work) 24/62 T. D. 3930'. Ran 188 jts. 5962' of 4 1/2" 10.50% Lone Star casing sec. 29750' KB, float collar 9 3933' KB, comented w/175 ex 50/50 pozmix 4 gol, 100 ex regular w/1.5% D-15, plug down 9 8:15 PM 24th. NOC REFLYED MAY 3 1 1962 CIL COM. COM. DIST. 3	NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO TEST WATER SH NOTICE OF INTENTION TO RE-DRILL OR R MOTICE OF INTENTION TO SHOOT OR ACII NOTICE OF INTENTION TO PULL OR ALICE	HUT-OFF	SUBSEQUENT I SUBSEQUENT I SUBSEQUENT I SUBSEQUENT I	REPORT OF SHOOT REPORT OF ALTERI REPORT OF RE-DRI REPORT OF ABAND	ING OR PACIFICATION ING CASING LLING OR REPAIR ONMENT	√ NEW-M£X13 0
Well No. 1 is located 790 ft. from N line and 790 ft. from E line of sec. 2 NE/4 NE/4 Sec. 28 27 N 12 N NAPM (K Sec. and Sec. No.) (Twp.) (Bange) (Moridian) New Mexico (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 5823 ft. Si. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cering points, and all other important proposed work) 14/62 T. D. 5930°. Ran 188 jts. 5962° of 4 1/2° 10.50% Lone Star casing second 19930° KB, float cellar 0 5933° KB, comented w/175 ax 30/50 pozmix gel, 100 ax regular w/1.5% D-15, plug down 0 8:15 PM 24th. ECC REFIVED MAY 3 1 1962 CIL CON. COM DIST. 3	(INDICATE AR	BOVE BY CHECK MARK I	NATURE OF REPORT	NOTICE, OR OTHE	R DATA)	<u></u> - <u> </u>
NE/4 NE/4 Sec. 28 27 N 12 N NAPM (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian) Resin Pakerta Sen Juan New Mexico (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 5823 ft. GL DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereing points, and all other important proposed work) 24/62 T. D. 5930°. Ran 188 jts. 5962° of 4 1/2° 10.50% Lone Star casing second county of the collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 5933° KB, comented w/175 ex 30/50 pozmix of 5950° KB, float collar of 595				May 28		, 19 .62
Sen Juan (Field) (County or Subdivision) (State or Territory) (State or Territory) (State or Territory) (County or Subdivision) (State or Territory) (Details of WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereing points, and all other important proposed work) (24/62 T. D. 3630'. Ran 188 jts. 5962' of 4 1/2" 10.50% Lone Star casing see 5950' KB, float cellar 9 3933' KB, comented w/175 ex 50/50 pozmix 4 gel, 100 ax regular w/1.5% D-15, plug down 6 8:15 PM 24th. NOC (CIL COM. COM. COM. COM. COM. COM. COM. COM.	Well No. 1 is located	790 ft. from	$\left\{ egin{array}{c} N \\ K \end{array} \right\}$ line and	790 ft. fr	om $\left\{ egin{array}{c} \mathbf{E} \end{array} \right\}$ line of	sec. 28
(Field) (County or Subdivision) The elevation of the derrick floor above sea level is 5823. ft. GL DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, certain points, and all other important proposed work) 14/62 T. D. 9830°. Ran 188 jts. 5962° of 4 1/2" 10.50% Lene Star casing sea 5930° kB, float cellar 9 5933° kB, comented w/175 ex 50/50 pozmix 4 ge1, 100 ax regular w/1.5% D-15, plug down 0 8:15 PM 24th. MCC REFERENCE MAY 3 1 1962 CIL COM. COM. DIST. 3 Lunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	ME/4 ME/4 Sec. 28	27 N	12 W	(Meridian)		
(Field) (County or subdivision) (County or s				(Distribut)	New Mexico	
DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereing points, and all other important proposed work) 14/62 T. D. 9930°. Ran 188 jts. 5962° of 4 1/2° 10.50% Lone Star casing see 99930° KB, float collar 9 5933° KB, comented w/175 ex 50/50 pozmix 4 gel, 100 ax regular w/1.5% D-15, plug down 9 8:15 PM 24th. NCC REFLYED MAY 3 1 1962 CIL CON. COM DIST. 3 I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	(Гієм)	(County of	Bubdivision)		(Desire of Territory)	
State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, certaing to the important proposed work) 14/62 T. D. 9930°. Ran 188 jts. 5962° of 4 1/2" 10.50% Lone Star casing see 9930° KB, float collar 9 5933° KB, comented w/175 ex 50/50 pozmix 4 gel, 100 ax regular w/1.5% D-15, plug down 9 8:15 PM 24th. NOC REFEVED MAY31 1962 CIL COM. COM DIST. 3 I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	The elevation of the derrick flo	or above sea lev	el is 5823	t. GL		
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.		DETAIL	LS OF WOR	K		
1. D. 9930'. Ran 188 jts. 5962' of 4 1/2" 10.50% Lone Star casing see 9930' KB, float celler 9 5933' KB, cemented w/175 ex 30/30 pozmix 4 gel, 100 ex regular w/1.5% D-15, plug down 9 8:15 PM 24th. MCC RECEVED MAY 3 1 1962 CIL COM. COM DIST. 3 I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	State names of and expected depths to obje	ective sands; show size	s, weights, and leng	ths of proposed ca	sings; indicate mud	ding jobs, cement
	e 9950° KB. float	cellar 0 593	13' KB. com	nted w/17:	RECEI MAY 3 1	1962 N. COM.
Company Southwest Production Company	I understand that this plan of work mu					
				ogical Survey befo	re operations may b	
Address 207 Petr. Club Plaza Original signed by						
Farmington, New Mexico By	Company Southwest Pr	oduction Comp		Or	jainal signed by	

GPO 852040

Title Superintendent