

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

REVISED

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SP-077952

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

J. C. Gordon "D"

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC. T., R., M., OR BLK. AND

SURVEY OR AREA

**SE 1/4, SE 1/4, Section 23,
T-27N, R-10W**

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

P. O. Box 480, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

840' FSL and 790' FBL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GK, etc.)

6274 (RDB)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) **Well History**

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐
☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above well was spudded on 7-22-64 and drilled to a depth of 356'. 8-5/8" casing was set at that depth with 225 sacks cement containing 2% calcium chloride. Cement circulated to surface. After waiting on cement tested casing with 1000 psi. Test OK. Reduced hole size to 7-7/8" and resumed drilling.

Well was drilled to a total depth of 6713'. 4-1/2" casing was set at that depth with stage collar at 4793. Cemented first stage with 350 sacks cement containing .6% gel, 2 pounds medium Tuf Plug per sack and followed by 100 sacks neat cement. Cemented second stage with 200 sacks cement containing 6% gel, 2 pounds medium Tuf Plug per sack. Pressured to 2000 psi. After waiting on cement tested casing with 3500 psi. Test OK.

Perforated 6614-37 with 4 shots per foot. Fracked these perforations with 38,304 gallons water containing 1% calcium chloride and 7 pounds J-2 per 1000 gallons and 40,000 pounds sand. Breakdown pressure 1100, average treating 3150 psi. Average injection rate 43.4 BPM. Bridge plug set at 6600 and tested with 3500 psi. Test OK. Perforated 6570-60, 6526-15 with 4 shots per foot. Fracked these perforations with 20,286 gallons water treated as above and containing 20,000 pounds sand. Breakdown pressure 1900, average treating 3400 psi. Average injection rate 35.2 BPM. Drilled out bridge plug and cleaned up well.

2-3/8" tubing landed at 6530' and well completed 8-25-64 as Basin Dakota Field Development Well. Preliminary test 3000 MCFD.

18. I hereby certify that the foregoing is a true and correct copy of the original signed by

FRED L. HOLLINGSWORTH

Fred L. Nabors, District Engineer

SIGNED

TITLE

DATE **September 29, 1964**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.