Form 3160-5 (June 1990)

(This space for Federal or State office use)

Conditions of approval, if any:

Approved by \_

## UNITED STATES DEPARTMENT OF THE INTERIOR BURLAU OF LAND MANAGEMENT

FORM APPROVED					
Budget Bur	eau No.	1904-0135			
Expires:	March 3	3 <b>V</b> . 1993			

5. Lease Designation and Serial No.

SF 077952-A

	_	
	ATTOES A	

CUMPRY MOTICES AN	D REPORTS ON WELLS	31 011332-A
Do not use this form for proposals to drill	6. If Indian, Allottee or Tribe Name	
	PERMIT - " for such proposals  IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well  Oil  Well  X Gas Well  Other  2. Name of Operator		8. Well Name and No. Gordon A 2
ENERGEN RESOURCES CORPORATION  3. Address and Telephone No. 2198 Bloomfield Highway, Farmingtor  4. Location of Well (Footage, Sec., T., R., M., or Survey De 1090' FSL, 990' FEL, Sec 24, T27N,	scription)	9. API Well No. 30-045-06336  10. Field and Pool, or exploratory Area Basin Dakota
		San Juan N.M.
	) TO INDICATE NATURE OF NOTICE, REPORT,	ONOTHENDATA
TYPE OF SUBMISSION  Notice of Intent	TYPE OF ACTION  Abandonment	Change of Plans
X Subsequent Report	Recompletion Plugging Back	New Construction Non-Routine Fracturing
Final Abandonment Notice	Casing Repair Altering Casing Other	Water Shut-Off Conversion to Injection Dispose Water
Describe Proposed or Completed Operations (Clearly state all give subsurface locations and measured and true vert	pertinent details, and give pertinent dates, including estimated date of startical depths for all markers and zones pertinent to this work.)*	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) any proposed work. If well is directionally drilled,
12/7/00 MIRU. ND wellhead, NU BOP. 6700' & circ. hole w/2% KCL. 12/8/00 Set packer @ 6700' & test r packer @ 3897'. RU Halliburton & sq 12/9/00 TOH with packer. TIH with 4 12/12/00 Drill cement to 4273'. Tes @ 3897'. 12/13/00 RU Halliburton. Resqueeze 12/14/00 TOH with packer. TIH with to 400# in 30 min. 12/15/00 TOH with bit. TIH with packer. 12/16/00 TOH with packer. TIH with 12/18/00 Test casing from 4150'-443 4-3/4" mill. 12/19/00 Tag retainer @ 6746', dril	Release tubing from retainer & TOH. TIH with etainer to 1000# - OK. Isolate casing leak fueeze with 100 sks. cement. RD Halliburton3/4" bit, tag cement @ 4020', drill to 4170 t casing to 700#, dropped to 300# in 30 min. with 100 sks. "B". RD Halliburton. bit, tag cement @ 4124', drill to 4589'. Tesker, set @ 3904'. RU Halliburton & resqueeze bit, tag cement @ 4150', drilled to 4431'. 1' to 700#. Drill cement to 4620'. TOH with 1 out retainer & clean out to 6975'. TOH. 59 jts. 2-3/8", 5-1/2" packer & 160 jts. 2-	From 4085'-4464'. Set  TOH. TIH with packer, set  st casing to 700#, dropped  with 100 sks. "B".  bit. TIH with
14. I hereby certify that the foregoing is true and correct		

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Title Drilling & Completion Foreman

# **2**77

Date 1/4/00

Date -

Title