	C=01.0C10.41	CHDVEV	se side)		eau No. 42-R N AND SERIAL
	ORY NOTICES AND Form for proposals to drill or to	REPORTS ON W		SF-030168- 6. IF INDIAN, ALLOTT	
(the not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)				7. UNIT AGREEMENT NAME	
WELL GAS WELL X	OTHER				A 1/4
2. NAME OF OPERATOR TENNECO OIL COMPANY				8. FARM OR LEASE NAME H. O. Watson	
3. ADDRESS OF OPERATOR	2 CONTAIN			9. WELL NO.	011
	ln Tower Bldg., Denv			2	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface				Basin Dakota	
	FNL and 790' FWL			Dd5 III Dd 11. SEC., T., R., M., OB SURVEY OR ARI	BLK. AND
14. PERMIT NO.	15. ELEVATIONS	Show whether DF, RT, GR, et	te.)	Sec. 22, T2 12. COUNTY OR PARIS	
	5828		·	San Juan	New Me
16.	Check Appropriate Box	To Indicate Nature o	Notice, Report, or	Other Data	
N(CTICE OF INTENTION TO:	1		QUENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CAS	SING W	ATER SHUT-OFF	REPAIRING	WELL
FRACTURE TREAT	MULTIPLE COMPLET		RACTURE TREATMENT	ALTERING	CASING
SHOOT OR ACIDIZE	ABANDON*		HOOTING OR ACIDIZING	MUNDONAGA	ENT* X
REPAIR WELL (Other)	CHANGE PLANS		Other)(Note: Report resul	ts of multiple completion	n on Well
Snotted 20 car	cks cement plugged f	from 5934' - 566	54'.	LI PORT	
Spotted 20 sac Spotted 20 sac Cut off 4 1/2" and welded pla Cleaned locati	cks cement plugged focks cement plugged focks cement plugged focks as a constant of all debris, focks as required.	form 1445' - 117)' cement plug '	75'. inside 4 1/2"	nd 8 5/8% casi DIST led pits, blad	7
Spotted 20 sac Spotted 20 sac Cut off 4 1/2" and welded pla Cleaned locati	cks cement plugged f cks cement plugged f " casing. Placed 20 ate over 8 5/8" stub ion of all debris, f	form 1445' - 117)' cement plug '	75'. inside 4 1/2"	DIT COLA	7
Spotted 20 sac Spotted 20 sac Cut off 4 1/2" and welded pla Cleaned locati	cks cement plugged f cks cement plugged f " casing. Placed 20 ate over 8 5/8" stub ion of all debris, f	form 1445' - 117)' cement plug '	75'. inside 4 1/2"	led pits, blad	7
Spotted 20 sac Spotted 20 sac Cut off 4 1/2" and welded pla Cleaned locati	cks cement plugged f cks cement plugged f " casing. Placed 20 ate over 8 5/8" stub ion of all debris, f	form 1445' - 117)' cement plug '	inside 4 1/2"	led pits, blad	7
Spotted 20 sac Spotted 20 sac Cut off 4 1/2" and welded pla Cleaned locati location and s	cks cement plugged f cks cement plugged f " casing. Placed 20 ate over 8 5/8" stub ion of all debris, f	form 1445' - 117 o' cement plug o	JUN 86 1 U. S. CECLO	led pits, blad	ed
Spotted 20 sac Spotted 20 sac Cut off 4 1/2" and welded pla Cleaned location and s	cks cement plugged focks cement plugged focks cement plugged focks are over 8 5/8" stubble over 8 5/8" stu	Form 1445' - 117	JUN 86 1 U. S. CECLO	led pits, blad	ed

S.P 9 1975

E. J. McGRATH

*See Instructions on Reverse Side

DISTRICT, ENGINEER