UNITED STATES

5.	LEASE
•	NM 02861
6.	IF INDIAN, ALLOTTEE OR TRIBE NAME
	·
7.	UNIT AGREEMENT NAME
	•

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	NM 02861 6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME			
1. oil gas well other	8. FARM OR LEASE NAME Lodewick 9. WELL NO.			
2. NAME OF OPERATOR El Paso Natural Gas Company	#3 10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR P.O. Box 289, Farmington, New Mexico 87401	Fulcher Kutz P.C. 11. SEC., T., R., M., OR BLK. AND SURVEY OR			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 990'N, 990'W	AREA Sec. 19, T-27-N, R-9-W 12. COUNTY OR PARISH 13. STATE			
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico 14. API NO.			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6524' Gr.			
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)	(NOT): Report results of multiple completion or, zane change on Form 9-330.)			
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinents.)	e all pertinent details, and give pertinent dates, irectionally drilled, give subsurface locations and it to this work.)*			
1) Circulate the well with mud. 2) Spot a plug from TD to 2110' to cover formation (50 sk). 2060 1440' 3) Perforate the 5 1/2" casing at 1660' a	ind squeeze cement to 1400 ft.			
Spot a plug from 1660', to 1400', to cov (70 sk). 1440' to 1340' to cov	er the Kirtland and Ojo Alamo te			

4) Perforate the casing at 201' and squeeze cement to the surface in the $8\ 5/8$ "-5 1/2" annular space and spot a plug from 201 ft. to surface inside the 5 1/2" casing.

5) Install a dry hole marker.

Subsurface Safety Valve: Manu. and Type		Set @	Ft.
18. I hereby certify that the foregoing is flue and correct Production SIGNED TILE Engineer	. DATE	June 9, 1982	Table 1
APPROVED BY HIM 1 0 56 11 TITLE) DATE	E	
JAMES F. SIMS NMOCC DISTRICT ENGINEER		3 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	
*See Instructions on Reverse Side			