*

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4. Approval expires 12-31-60.

Land Office Santa Fe

Lease No. SF-077382

Unit U. J.A. R. . Hargrave M

OTICE OF INTENTION TO DRILL	SUBSECUEN	T REPORT OF WATER SHUT-OFF	X	
TICE OF INTENTION TO CHANGE PLANS	1 5	T REPORT OF SHOOTING OR ACIDI	71NG	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.		: II	T REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		1 11	T REPORT OF RE-DRILLING OR REF	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		1 1)	T REPORT OF ABANDONMENT	1
OTICE OF INTENTION TO PULL OR ALTER CASING.		i 10	TARY WELL HISTORY	
TICE OF INTENTION TO ABANDON WELL				·
(INDICATE AB	OVE BY CHECK MA	ARK NATURE OF REPOR	RT, NOTICE, OR OTHER DATA)	
a.k. E. P. Hargrave of	(#	Farmingt	on, New Mexico Sept	ember 4
No. 1 is located	790 ft fre	om Tiline on	. 790 (. c	. 74
			d 790 ft. from W lir	ne of sec.
/4 of Section 16	1-27-4	£-10-÷	N.M.P.M.	
gels Peak Dakota	(Twp.)	(Range)	(Meridian)	
(Field)		ty or Subdivision)	(State or Terri	+
				wiy)
elevation of the derrick floo	r above sea	level is	ft. (Ground Level)	
	DET	ALLS OF WOR	17	
names of and expected depths to object		AILS OF WOR		
	tive sands; show ing points, and a	sizes, weights, and ler ll other important pro	ngths of proposed casings; indicate posed work)	_
added 12-1/4" hole on the at 373' with 250 eac	tive sands; showing points, and al	sizes, weights, and ler ill other important pro 1959 and dr	rights of proposed casings; indicate apposed work) 111ed to 373'. 6-5	/8" casing w
edded 12-1/4" hole on t at 373" with 250 eac roulated. After waiti	tive sands; showing points, and al August 29, ks coment	sizes, weights, and ler ill other important pro 1959 and dr containing 2	rights of proposed casings; indicate apposed work) 111sd to 373'. 6-5 5 calcium chloride.	/8" casing a
added 12-1/4" hole on t at 373' with 250 eac roulated. After waiti pai for fifteen minu	tive sands; showing points, and al August 29, ks coment ng on come too which	sizes, weights, and ler ill other important pro 1959 and dr containing a ent, casing a hald with me	gths of proposed casings; indicate opposed work) 111ed to 373'. 6-5 2 calcium chloride. Ind water shut off we indicate of proposed works.	/8" casing a
edded 12-1/4" hole on t at 373" with 250 eac roulated. After waiti O pai for fifteen minu	tive sands; showing points, and al August 29, ks coment ng on come too which	sizes, weights, and ler ill other important pro 1959 and dr containing a ent, casing a hald with me	gths of proposed casings; indicate opposed work) 111ed to 373'. 6-5 2 calcium chloride. Ind water shut off we indicate of proposed works.	/8" casing m
added 12-1/4" hole on t at 373' with 250 eac roulated. After waiti D pai for fifteen minu	tive sands; showing points, and al August 29, ks coment ng on come too which	sizes, weights, and ler ill other important pro 1959 and dr containing a ent, casing a hald with me	gths of proposed casings; indicate opposed work) 111ed to 373'. 6-5 2 calcium chloride. Ind water shut off we indicate of proposed works.	/8" casing m
added 12-1/4" hole on t at 373' with 250 eac roulated. After waiti D pai for fifteen minu	tive sands; showing points, and al August 29, ks coment ng on come too which	sizes, weights, and ler ill other important pro 1959 and dr containing a ent, casing a hald with me	gths of proposed casings; indicate opposed work) 111ed to 373'. 6-5 2 calcium chloride. Ind water shut off we indicate of proposed works.	/8" casing m
names of and expected depths to object the second s	tive sands; showing points, and al August 29, ks coment ng on come too which	sizes, weights, and ler ill other important pro 1959 and dr containing a ent, casing a hald with me	gths of proposed casings; indicate opposed work) 111ed to 373'. 6-5 2 calcium chloride. Ind water shut off we indicate of proposed works.	/8" casing m
added 12-1/4" hole on t at 373' with 250 eac roulated. After waiti D pai for fifteen minu	tive sands; showing points, and al August 29, ks coment ng on come too which	sizes, weights, and ler ill other important pro 1959 and dr containing a ent, casing a hald with me	gths of proposed casings; indicate opposed work) 111ed to 373'. 6-5 2 calcium chloride. Ind water shut off we indicate of proposed works.	/8" casing w
edded 12-1/4" hole on t at 373" with 250 eac roulated. After waiti O pai for fifteen minu	tive sands; showing points, and al August 29, ks coment ng on come too which	sizes, weights, and ler ill other important pro 1959 and dr containing a ent, casing a hald with me	gths of proposed casings; indicate opposed work) 111ed to 373'. 6-5 2 calcium chloride. Ind water shut off we indicate of proposed works.	/8" casing m
added 12-1/4" hole on t at 373' with 250 eac roulated. After waiti pai for fifteen minu	tive sands; showing points, and al August 29, ks coment ng on come too which	sizes, weights, and ler ill other important pro 1959 and dr containing a ent, casing a hald with me	gths of proposed casings; indicate opposed work) 111ed to 373'. 6-5 2 calcium chloride. Ind water shut off we indicate of proposed works.	/8" casing a
added 12-1/4" hole on t at 373' with 250 eac roulated. After waiti pai for fifteen minu	tive sands; showing points, and al August 29, ks coment ng on come too which	sizes, weights, and ler ill other important pro 1959 and dr containing a ent, casing a hald with me	gths of proposed casings; indicate opposed work) 111ed to 373'. 6-5 2 calcium chloride. Ind water shut off we indicate of proposed works.	/8" casing a
added 12-1/4" hole on t at 373' with 250 each roulated. After waiting pai for fifteen minus Rueed hole to 7-7/8" m	tive sands; showing points, and al August 29, ks coment ng on come tos which 373 and	sizes, weights, and ler ill other important pro 1959 and dr containing 2 ent, easing a held with no recurse dri	illed to 373'. 6-5 salcium chloride. ind water shut off w indication of pres lling operations	/8" casing w Coment ers tested w sure drop.
edded 12-1/4" hole on t at 373' with 250 ead roulated. After waiti pai for fifteen minus succed hole to 7-7/8" m	tive sands; showing points, and al August 29, ks coment ng on come too which 373 and	sizes, weights, and ler ll other important property of the containing a containing	illed to 373'. 6-5 salcium chloride. ind water shut off w indication of pres lling operations	/8" casing w Coment ers tested w sure drop.
edded 12-1/4" hole on t at 373" with 250 eac roulated. After waiti O pai for fifteen minu	tive sands; showing points, and al August 29, ks coment ng on come too which 373 and	sizes, weights, and ler ll other important property of the containing a containing	illed to 373'. 6-5 salcium chloride. ind water shut off w indication of pres lling operations	/8" casing w Coment ers tested w sure drop.

Company	Pan American Petroleum Corporati	Lon
Address	Box 487	
	Farmington, New Mexico	OHIGINAL SIGNED R. M. Baber :
	Attn: L. O. Speer, Jr.	Title Area Sagineer