


STATE OF NEW MEXICO
OIL CONSERVATION
COMMISSION
DISTRICT NO. 3
Phone 99 P. O. Box 697
AZTEC, NEW MEXICO

(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____

Lease No. _____

Unit _____



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____
NOTICE OF INTENTION TO ABANDON WELL _____	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

E. C. KATZ

Well No. 1 is located 770 ft. from N line and 990 ft. from E line of sec. _____
34 1/4 Section 16 27 North, 12 East E.M.P.A.

16 (Sec. No.) San Juan County (Meridian) New Mexico (State or Territory)

16 (Field) San Juan County (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-
Set 4-5/8" 140 casing at 180' and cement with 75 sacks regular cement. and 48 hrs.
Set 3 1/2" 140 J-35 casing on top of Pictured Cliff Sand, 5 1/2" equipped with Baffle
Collar and Float Shoe and two Centralizers. Run Temperature Survey to determine
top of cement behind 5 1/2". 400 72 hrs. Core the entire Pictured Cliffs Sand.
Run Schlumberger Electrical Log and Microlog Pictured Cliff Sand, Farmington Sand,
and Fruitland Sand before setting production string. Straight hole test at 100'.
Maximum deviation one degree and at every 150' intervals to 1.0. with maximum
deviation of three degrees. Start 5' samples and drilling time at 800'. And
shall be conditioned to obtain good drilling samples. Steel Line Measurement at
1000' and before curing. 5 1/2" 140 J-35 casing to be set on top of Pictured Cliff
Sand after the hole has been reamed to bottom of sand. Clean out with cable tools
and test. Shoot with 3 quarts 300 per foot with no trap. Clean out to total
depth and run 1" siphon.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

THE AMERICAN OIL PRODUCING COMPANY

Company _____

Address _____
P. O. Box 3167
SALAMANCA CITY, CALIFORNIA

By [Signature]

Title District Superintendent

CENTRAL SURVEY
 DEPARTMENT OF THE INTERIOR
 UNITED STATES
 (SUBMIT IN TRIPLICATE)

SUBSEQUENT REPORT OF WATER SHUT-OFF	
SUBSEQUENT REPORT OF SHOOTING OR ACCIDENT	
SUBSEQUENT REPORT OF ALLEGED DAMAGE	
SUBSEQUENT REPORT OF RECKLING OR RESCUE	
SUBSEQUENT REPORT OF ABANDONMENT	
SUPPLEMENTARY WELL REPORT	

is located _____ line and _____ ft. from _____
(W) _____

The elevation of the barrier floor above sea level is _____ ft.

DETAILS OF WORK

[illegible]

I understand that this plan of work must receive approval from the Geological Survey before it can be carried out.

Company _____

Address _____

By _____

The _____