

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 19935. Lease Designation and Serial No.
SF 079115

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Tonkin 1

9. API Well No.

10. Field and Pool, or Exploratory Area

West Kutz Pictured Cliffs

11. County or Parish, State

San Juan, N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1970' FWL

13 - 27M - 12W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent☐ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug well by spotting Class B + 6% gel plugs as follows:

1. 100' plug across 7" casing shoe at 1661 to cover top of Pictured Cliffs @ 1670.
2. 100' plug inside 7" 1300 - 1400 across Fruitland @ 1350.
3. Perforate 50' below 10" casing @ 655' and spot 100' plug inside and outside.
4. Spot 50' surface plug.

Plugs will be ^{SEPARATED} spotted with 40 sec/qt. viscosity, 8.34 lb./gal. mud. Virgin reservoir pressure for the West Kutz Pictured Cliffs was 500 psi, in 1950 and the Fruitland has a 250 psi bottom hole pressure. The 8.34 lb./gal. mud will provide well control.

Signed

John Alexander

Title

Operations Mgr.

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

*151000*APPROVED
AS AMENDED

JUL 8 1992

AREA MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side