

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 17701
Unit 1850

1950

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 10, 1959

Well No. Lodewick #4 is located 1850 ft. from N line and 2300 ft. from W line of sec. 18

SE NW Sec. 18
(1/4 Sec. and Sec. No.)
Angels Peak Dakota
(Field)

27N
(Twp.)
9W
(Range)
San Juan
(County or Subdivision)


N 36° 15' W
(Meridian)
New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6241 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded w/Rotary tools 2 p.m. 8-8-59. Drilling 13-3/4" hole to 450 feet. Ran 12 jts. 424.20' of 10-3/4" O.D. 8rd thd. 32.75# W-40, R-2 & R-3, STAG. Nat. snls casing set at 442.20' K.B. 13.90' K.B. to ground level. Cemented with 250 sx. regular cement, 2% Calcium Chloride, circulated to surface. Plug down 5 a.m. 8-9-59. WOC 24 hours. Tested plug w/500 psi for 30 min. Test OK.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company TRILL STATES NATURAL GAS COMPANY

Address P. O. Box 67

Farmington, New Mexico

By Original Signed By John Carothers

Title Assistant District Supt.