5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

DISTRICT ENGINEER

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	SF 078935
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME
	8. FARM OR LEASE NAME
1. oil gas 🔽	Thompson "C"
well well other	9. WELL NO.
2. NAME OF OPERATOR	# 4
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	W. Kutz Pictured Cliffs
P.O. Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	AREA NE Sec. 10, T-27-N, R-12-W
AT SURFACE: 990'N, 990'E, Sec. 10, T27N, R12W	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: a/a AT TOTAL DEPTH:	San Juan New Mexico
a/a	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5944' DF
TEST WATER SHUT-OFF	
FRACTURE TREAT	The state of the s
SHOOT OR ACIDIZE	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING U SEP VV I	(NOTE: Repert results of multiple completion or zone change on Form 9–330.)
CHANGE ZONES	
ABANDON*	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen Plug well, non-productive. 	e all pertinent details, and give pertinent dates, irectionally drilled, give subsurface locations and t to this work.)*
	1 (011)
3) Use 40 sx inside $5\frac{1}{2}$ " csg. to set plug ac 1555'-1228' (327')	ross Fruitiand - Pictured Cliffs
	sumf 11/126 as from batton of
	- Suri. W/120 SX Irom Dollom OI
Ojo Alamo to surface and inside $5\frac{1}{2}$ " csg 5) Cut csg 4' below surface, weld plate on	aca ctub. Não dour hala mantean
above surface.	csg stim No-dry note marker
6) Use 9.0 - 9.2 1b mud between plugs.	/ RHITA
	~46/// / \\
i la	SEP 13 1982 DIST COMP Set ®
	1982
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
Production	
SIGNED Aller Faler TITLE Engineer	DATE September 8, 1982
ADDOVE TATHIS space for Federal or State offi	ce use)
APPROVICE	
APPROVED BY TITLE TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE
SEP, 20 1982	<u>.</u>
Jahran Kelle	···
FORJAMES F. SIMS	

See Instructions on Reverse Side