

LOCATE WELL CORRECTLY

U. S. LAND OFFICE Santa Fe
SERIAL NUMBER 046563

LEASE OR PERMIT TO PROSPECT
U.S.A. Prod. Federal

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

PRIOR
 JUN 22 1953
 U. S. GEOLOGICAL SURVEY
 FARMINGTON, N. M.

LOG OF OIL OR GAS WELL

Company Stanolind Oil and Gas Company Address Box 591, Tulsa, Oklahoma
 Lessor or Tract Fred Fernal "F" Field Pulcher Kato-
 Pictured Bluffs State New Mexico
 Well No. 1 Sec 2 T7-N 20-W Meridian NMPM County San Juan
 Location 1850 ft. {N } of S Line and 2450 ft. {W } of E Line of Section 2 Elevation 5774

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed ER Help

Date **June 18, 1953** Title **Field Superintendent**

The summary on this page is for the condition of the well at above date

Commenced drilling February 26, 1953 Finished drilling March 5, 1953

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 1903 to 1905 (a) No. 4, from _____
No. 2, from _____ to _____ No. 5, from _____
No. 3, from _____ to _____ No. 6, from _____ to 10 1903

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
8-5/8"	2.2	8	Made in Germany	107	Outside				
5-1/2"	2.7	8	Booth	1972	Outside				
1-1/4"	2.3	8	Booth	1972	Outside		1960	1972	

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
8-5/8"	119	75	Displacement		
5-1/2"	1913	75	Displacement		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth set

Adapters—Material Size

SHOOTING RECORD

[illegible]

TOOLS USED

Rotary tools were used from 0 feet to 1988 feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

² DATES

March 6, 1953 Put to producing March 26, 1953

The production for the first 24 hours was _____ barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, °Bé. _____

If gas well, cu. ft. per 24 hours 1,890,000 Gallons gasoline per 1,000 cu. ft. of gas _____

EMPLOYEES

E. E. Barnard, Driller L. E. Rhoden, Driller
D. S. Bond, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	1774	1774	Shale and sand
1774	1903	129	Shale, sand and coal
1903	1988	85	Sand (Top Pictured Cliffs - 1903)

