REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON\* (other)

## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Form 9–331 Dec. 1973	Budget Bureau No. 42-R1424		
UNITED STATES	5. LEASE		
DEPARTMENT OF THE INTERIOR	SF 078390		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME		
	Jones A		
well gas X other	9. WELL NO.		
2. NAME OF OPERATOR	5A		
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Blanco Mesa Verde, Blanco PC Ext.		
Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec. 13, T-28-N, R-8-W N.M.P.M.		
AT SURFACE: 1180 N, 1815 W	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL:	San Juan New Mexico		
AT TOTAL DEPTH:	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6363' GL		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF   EDACTURE TREAT			

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 3299'. Ran 86 joints 7", 20#, K-55 intermediate casing 3288' set at 3299' Cemented w/ 289 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 2500'.

1-12-80: TD 5631'. Ran 75 joints 4 1/2", 10.5#, KS casing liner 2459' set 3172-5631' Float collar set at 5614'. Cemented w/431 cu. ft. cement.

QC 18 hours. JAN 18196.

Subsurface Safety Valve: Manu. and Typ	e		Set @	Ft.
18. I hereby certify that the foregoing is	true and correct			
18. I hereby certify that the foregoing is	πιτιε Drilling Clerk	DATE	January 14, 19	80
	(This space for Federal or State office	use)		
APPROVED BY	TITLE	DATE .	· · · · · · · · · · · · · · · · · · ·	
CONDITIONS OF APPROVAL, IF ANY:	NMOCC		ACCEPTED	TECORD

\*See Instructions on Reverse Side

JAN 17'80

FARMINGTON DISTRICT