Budget	Bureau	No.	42-R358.4
Approv	al expire	s 12-	31-60.

Form 9-331 a (Feb. 1951)						

(SUBMIT IN TRIPLICATE)

UNITED STATES **DEPARTMENT OF THE INTERIOR** GEOLOGICAL SURVEY

Land Office		
Lease No.	0/2	02
Unit	Joh	eston

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPOI	RT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE P	PLANS	SUBSEQUENT REPOR	T OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WAT	TER SHUT-OFF	SUBSEQUENT REPOR	RT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL	OR REPAIR WELL	SUBSEQUENT REPOR	T OF RE-DRILLING OR REPAIR	<u> </u>
NOTICE OF INTENTION TO SHOOT OF	R ACIDIZE	SUBSEQUENT REPOR	T OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR	ALTER CASING	SUPPLEMENTARY W	ELL HISTORY	
NOTICE OF INTENTION TO ABANDON	WEL,L	46467 7746		
(INDICA	ATE ABOVE BY CHECK MARK N.	ATURE OF REPORT, NOTI	CE, OR OTHER DATA)	
			May 14	, 19 .57
Well No. 6-x is locat	ted 1168 ft. from	S line and 10	ft. from line of	sec. 10
SW Section 10	28	(a)	I.M.P.N.	
(1/2 Sec. and Sec. No.)			Meridian)	Mississi
Blanco	San Juan		New Mexico	
(Field)	(County or S	Subdivision)	(State or Territory)	MAY 17 1057
TI 1 (.1 1	a 1 1 1	· Kaka c	10	Off Con
The elevation of the derrick	floor above sea leve	l is it.		COM. COM
	DETAIL			UIST o
	Dr. (All.)	S OF WORK	'	J., Q
(State names of and expected depths to		S OF WORK		
(State names of and expected depths to	o objective sands; show sizes,		proposed casings; indicate mude work)	ding jour
(State names of and expected depths to	o objective sands; show sizes,	weights, and lengths of	proposed casings; indicate mudo work)	ding Joseph
5-1-57. Total Depti	o objective sands; show sizes, ing points, and all others.	weights, and lengths of er important proposed v	· . Water fractured	
	o objective sands; show sizes, ing points, and all others.	weights, and lengths of er important proposed v	· . Water fractured	
5-1-57. Total Depti Point Lockout perfo 4924-35' (2 shots p	o objective sands; show sizes, ing points, and all other hands of the same of	weights, and lengths of er important proposed ack T.B. 4961 720-36; 4616 ,000 gallons	'. Water fractured 3-46'; 4888-4902' a mat water and 70,00	i md
5-1-57. Total Depti Point Lockout perfor 4924-35' (2 shots person. Breakdown per	h 5012'. Ping be rated intervals or foot) with 76	weights, and lengths of er important proposed ack T.B. 4961 4720-36'; 4614 ,000 gallons a ginna treating	'. Water fractured 3-46'; 4888-4902' a mak weter and 70,00 ; pressure 1600j.	i md
5-1-57. Total Depti Point Lockout perfor 4924-35' (2 shots present. Breakdown pro Average treating pro	h 5012'. Ping be rated intervals or foot) with 76	weights, and lengths of er important proposed ack T.B. 4961 4720-36'; 4614 ,000 gallons a ginna treating	'. Water fractured 3-46'; 4888-4902' a mak weter and 70,00 ; pressure 1600j.	i md
5-1-57. Total Depti Point Lockout perfor 4924-35' (2 shots person. Breakdown per	h 5012'. Ping be rated intervals or foot) with 76	weights, and lengths of er important proposed ack T.B. 4961 4720-36'; 4614 ,000 gallons a ginna treating	'. Water fractured 3-46'; 4888-4902' a mak weter and 70,00 ; pressure 1600j.	ind.
5-1-57. Total Depti Point Lockout perfor 4924-35' (2 shots present. Breakdon pr Average treating pr	h 5012'. Ping be rated intervals or foot) with 76	weights, and lengths of er important proposed ack T.B. 4961 4720-36'; 4614 ,000 gallons a ginna treating	'. Water fractured 3-46'; 4888-4902' a mak weter and 70,00 ; pressure 1600j.	ind.
5-1-57. Total Depti Point Lockout perfor 4924-35' (2 shots present. Breakdon pr Average treating pr	h 5012'. Ping be rated intervals or foot) with 76	weights, and lengths of er important proposed ack T.B. 4961 4720-36'; 4614 ,000 gallons a ginna treating	'. Water fractured 3-46'; 4888-4902' a mak weter and 70,00 ; pressure 1600j.	ind.
5-1-57. Total Depti Point Lockout perfor 4924-35' (2 shots present. Breakdon pr Average treating pr	h 5012'. Ping be rated intervals or foot) with 76	weights, and lengths of er important proposed ack T.B. 4961 4720-36'; 4614 ,000 gallons a ginna treating	'. Water fractured 3-46'; 4888-4902' a mak weter and 70,00 ; pressure 1600j.	ind.
5-1-57. Total Depti Point Lockout perfor 4924-35' (2 shots present. Breakdon pr Average treating pr	h 5012'. Ping be rated intervals or foot) with 76	weights, and lengths of er important proposed ack T.B. 4961 4720-36'; 4614 ,000 gallons a ginna treating	'. Water fractured 3-46'; 4888-4902' a mak weter and 70,00 ; pressure 1600j.	ind.
5-1-57. Total Depti Point Lockout perfor 4924-35' (2 shots present. Breakdon pr Average treating pr	h 5012'. Ping be rated intervals or foot) with 76	weights, and lengths of er important proposed ack T.B. 4961 4720-36'; 4614 ,000 gallons a ginna treating	'. Water fractured 3-46'; 4888-4902' a mak weter and 70,00 ; pressure 1600j.	ind.
5-1-57. Total Depti Point Lockout perfor 4924-35' (2 shots present. Breakdon pr Average treating pr	h 5012'. Ping be rated intervals or foot) with 76	weights, and lengths of er important proposed ack T.B. 4961 4720-36'; 4614 ,000 gallons a ginna treating	'. Water fractured 3-46'; 4888-4902' a mak weter and 70,00 ; pressure 1600j.	ind.
5-1-57. Total Depti Point Lockout perfor 4924-35' (2 shots present. Breakdown pro Average treating pro	o objective sands; show sizes, ing points, and all other sands. Fing be rated intervals or foot) with 76, marked 1790f, marked 1600f. In	weights, and lengths of er important proposed values. T.B. 4961. 1720-36'; 4816,000 gallons a minus treating ajection rute.	water fractured 3-46'; 4888-4902' a mat water and 70,00; pressure 1600%. 55.5 bbls./min. F	i md lo# Lush
5-1-57. Total Depti Point Lockout perfor 4924-35' (2 shots present. Breakform pre Average treating pre 7000 gallons.	o objective sands; show sizes, ing points, and all other sands in the	weights, and lengths of er important proposed values. T.B. 4961. 1720-36; 4614,000 gallons a minute treating agention rate	water fractured 3-46'; 4888-4902' a mat water and 70,00; pressure 1600%. 55.5 bbls./min. F	i md lo# Lush
5-1-57. Total Depti Point Lockout perfor 4924-35' (2 shots present. Breakdown pro Average treating pro 7000 gallons.	o objective sands; show sizes, ing points, and all other sands in the	weights, and lengths of er important proposed values. T.B. 4961. 1720-36; 4614,000 gallons a minute treating agention rate	water fractured 3-46'; 4888-4902' a mat water and 70,00; pressure 1600%. 55.5 bbls./min. F	i md lo# Lush

U.S. GOVERNMENT PRINTING OFFICE: 1956-O-393560

Title Petroleum Engineer