

Correction

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

(See instructions on reverse side)

Form No. 42-1000

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	6. LEASE DESIGNATION AND SERIAL NO. NM-03380
2. NAME OF OPERATOR Tenneco Oil Company	7. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 1714, Durango, Colorado	8. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 790' ESL 2370' FEL 970'	9. FARM OR LEASE NAME Florance
14. PERMIT NO.	10. WELL NO. 64
15. ELEVATIONS (Show bottom of well, etc.) 6771' GR	11. FIELD AND POOL, OR WILDCAT Basin Dakota
	12. SEC. T. R. M., OR BLK. AND SURVEY OR AREA Sec. 17-T27N-R8W
	13. COUNTY OR PARISH San Juan
	14. STATE New Mexico

14. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☒	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☒	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-30-66 Rig up completion rig. Perforate 7417-7429' w/ 1 HPF and 7378-7380', 7372-7374' and 7354-7358' w/ 2 HPF. Acidized w/ 500 gals. mud acid. Frac w/ 70,000# sand and 100,000 gals. water. Set B.P. at 7326'. Perforate 7296-7304' and 7382-7388' w/ 2 HPF. Frac w/ 40,000# sand and 50,000 gals. water. C.O. B.P. to P.B.T.D. 7480'. Released rig 12-2-66. W.O. test. Ran 2-3/8" EUE tubing. Set at 7400'.



RECEIVED

DEC 9 1966

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.



18. I hereby certify that the foregoing is true and correct

SIGNED

Harold C. Nichols

TITLE Senior Production Clerk

DATE 12-8-66

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

5-USGS

1-Conoco

1-File

*See Instructions on Reverse Side