A,

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office NA	i
Lease No. 048567	
Unit Frontier Pool Unit	"E"

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER	SHUT-OFF	λ
NOTICE OF INTENTION TO CHANGE PLANS.		SUBSEQUENT REPORT OF SHOOT	ING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SH		SUBSEQUENT REPORT OF ALTER		
NOTICE OF INTENTION TO RE-DRILL OR RI		SUBSEQUENT REPORT OF RE-DRI	- 11 11 12 15 15 (数 1770)	-7
NOTICE OF INTENTION TO SHOOT OR ACID NOTICE OF INTENTION TO PULL OR ALTER		SUBSEQUENT REPORT OF ABAND	1111	
NOTICE OF INTENTION TO ABANDON WELL	1	SUPPLEMENTARY WELL HISTORY	·	
			42 - 1 - 1	
(INDICATE ABO	OVE BY CHECK MARK NATU	RE OF REPORT, NOTICE, OR OTHER	R DATA)	 ; :: '5\
			Hune 220 11 10	AN
			7000 X2 19) <u>av</u>
7-II NJ	790 0 0 4	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	(E),.	
/ell No. is located	S	line and 1030 ft. fr	om line of sec.	k
W/4 SE/4 : ection 4	27:\(\) (Rang	(Meridian)	A CONTRACT OF THE CONTRACT OF	
(1/2 Sec. and Sec. No.) Indesignated Gallyp & Dakot	(Twp.) (Rang	e) (Meridian)	Zoli Fill	٠.
(Field)	(County or Sub	livision)	(State or Territory)	Ì
		6101	II HIDO	f
he elevation of the derrick floo	r above sea level is	6 0191 ft.	JUN 28 1960	
J.J. WILLIAM OF THE GETTICK HOO				
	DETAILS	OF WORK	FE CON COM	1 .
	DETAILS	OF WORK	CON, COM	I. /
itate names of and expected depths to objec	ctive sands; show sizes, we	OF WORK Ights, and lengths of proposed ca mportant proposed work)	Sings; indicate mudding obs. co	l, hent-
itate names of and expected depths to object ine 10, 1953 Total Depth 67	ctive sands; show sizes, we ing points, and all other i	ghts, and lengths of proposed ca mportant proposed work)	sings; indicate mudding the, co	hent-
itate names of and expected depths to object ine 10, 1950 Total Depth 67 Ran 32 joints, 7", 23	tive sands; show sizes, we ing points, and all other i 53°.	ghts, and lengths of proposed camportant proposed work)	sings; indicate mudding be, co	hent-
itate names of and expected depths to object ine 10, 1953 Total Depth 67 Ran 32 joints, 7", 23 asing (5433') set at 6746'.	tive sands; show sizes, we ing points, and all other i 53'. .00*, N-80 Casi	ng (1292') and 176 jonented with 100 sack	sings; indicate mudding be, co	hent-
itate names of and expected depths to object ine 10, 1953 Total Depth 67 Ran 32 joints, 7", 23 asing (5433') set at 6746'. acks Pozmix, 2% gel, 25# G	tive sands; show sizes, we ing points, and all other i 53°. .00%, N-80 Casi Lower stage certisonite per sac	ng (1292') and 176 jonented with 100 sack	sings; indicate mudding be, co	hent-
itate names of and expected depths to object the 10, 1950 Total Depth 67 Ran 32 joints, 7", 23 using (5433') set at 6746'. Acks Pozmix, 2% gel, 25# Griela 1000#/30 Minute	tive sands; show sizes, we ing points, and all other i 53'. .00*, N-80 Casi Lower stage certification its per saciss.	ng (1292') and 176 jonested with 100 sack	sings; indicate mudding be, co	hent-
itate names of and expected depths to object the 10, 1953 Total Depth 67 Ran 32 joints, 7", 23 using (5433') set at 6746'. Acks Pozmix, 2% gel, 25# Gifeld 1900#/30 Minute Top of dement by cale	tive sands; show sizes, we ing points, and all other i 53°. 1.00*, N-80 Cssi Lower stage certilsonite per saciss. culation at 4900°	ng (1292') and 176 jonented with 100 sack	sings; indicate mudding be, continued in the state of the	S:
itate names of and expected depths to object the 10, 1950 Total Depth 67 Ran 32 joints, 7", 23 asing (5433') set at 6746'. See Pozmix, 2% gel, 25# Griela 1000#/30 Minute Top of dement by calconnected upper stage	tive sands; show sizes, we ing points, and all other i 53°. 1.00*, N-80 Casi Lower stage certisonite per sacins. culation at 4900° through two-st	ng (1292') and 176 jonented with 100 sack	sings; indicate mudding be, continued in the state of the	S:
itate names of and expected depths to object the 10, 1950 Total Depth 67 Ran 32 joints, 7", 23 asing (5433') set at 6746'. See Pozmix, 2½ gel, 25# Griela 1000#/30 Minute Top of dement by calc Centented upper stage field 1000#/30 Minute	tive sands; show sizes, we ing points, and all other i 53'. .00*, N-80 Cssi Lower stage cervilsonite per sacces. culation at 4900's through two-stages.	ng (1292°) and 176 jonested with 100 sack	sings; indicate mudding be, continued in the state of the	S:
State names of and expected depths to object ine 10, 1953 Total Depth 67 Ran 32 joints, 7", 23 asing (5433") set at 6746". acks Pozmix, 2% gel, 25# G Held 1000#/30 Minute Top of dement by calc	tive sands; show sizes, we ing points, and all other i 53'. .00*, N-80 Cssi Lower stage cervilsonite per sacces. culation at 4900's through two-stages.	ng (1292°) and 176 jonested with 100 sack	sings; indicate mudding be, continued in the state of the	S:
itate names of and expected depths to object the 10, 1950 Total Depth 67 Ran 32 joints, 7", 23 asing (5433') set at 6746'. See Pozmix, 2½ gel, 25# Griela 1000#/30 Minute Top of dement by calc Centented upper stage field 1000#/30 Minute	tive sands; show sizes, we ing points, and all other i 53'. .00*, N-80 Cssi Lower stage cervilsonite per sacces. culation at 4900's through two-stages.	ng (1292°) and 176 jonested with 100 sack	sings; indicate mudding be, continued in the state of the	S:
itate names of and expected depths to object the 10, 1950 Total Depth 67 Ran 32 joints, 7", 23 asing (5433') set at 6746'. Acks Pozmix, 2½ gel, 25# Griela 1000#/30 Minute Top of dement by calcomented upper staginged 1000#/30 Minute	tive sands; show sizes, we ing points, and all other i 53'. .00*, N-80 Cssi Lower stage cervilsonite per sacces. culation at 4900's through two-stages.	ng (1292°) and 176 jonested with 100 sack	sings; indicate mudding be, continued in the state of the	S:
tate names of and expected depths to object ne 10, 1950 Total Depth 67 Ran 32 joints, 7", 23 using (5433") set at 6746". It is possible to 1000*/30 Minute Top of dement by calculated upper stage iteld 1000*/30 Minute Top of dement by calculated upper stage iteld 1000*/30 Minute Top of dement by calculated upper stage iteld 1000*/30 Minute	tive sands; show sizes, we ing points, and all other is 53°. .00\$, N-80 Casi Lower stage certilsonite per sacies. culation at 4900° through two-stage. culation at 1600°	ights, and lengths of proposed camportant proposed work) ng (1292') and 176 journmented with 100 sack i.	ints, 7", 23.00#, Just regular cement, 1	S: UU
tate names of and expected depths to object ne 10, 1950 Total Depth 67 Ran 32 joints, 7", 23 using (5433') set at 6746'. It is possible to the context of th	tive sands; show sizes, we ing points, and all other i 53°. 1.00°, N-80 Casi Lower stage certisonite per sacios. culation at 4900° through two-stage. culation at 1600°	ights, and lengths of proposed camportant proposed work) ing (1292°) and 176 journated with 100 sack i. Lige collar set at 220°	ints, 7", 23.00#, Just regular cement, 1	S: UU
tate names of and expected depths to object ne 10, 1950 Total Depth 67 Ran 32 joints, 7", 23 using (5433") set at 6746". It is possible to 1000#/30 Minute Top of dement by calculated upper stage iteld 1000#/30 Minute Top of dement by calculated upp	tive sands; show sizes, we ing points, and all other i 53°. 1.00°, N-80 Casi Lower stage certisonite per sacios. culation at 4900° through two-stage. culation at 1600°	ights, and lengths of proposed camportant proposed work) ing (1292°) and 176 journated with 100 sack i. Lige collar set at 220°	ints, 7", 23.00#, Just regular cement, 1	S: UU
itate names of and expected depths to object the 10, 1950 Total Depth 67 Ran 32 joints, 7", 23 asing (5433') set at 6746'. Acks Pozmix, 2% gel, 25* Griela 1000*/30 Minute Top of cement by calc Cemented upper stage iteld 1000*/30 Minute Top of cement by calc limit in the company of cement by calc limits. Top of cement by calc limits are also of cement by calc limits.	tive sands; show sizes, we ing points, and all other i 53°. 1.00°, N-80 Casi Lower stage certileonite per sactification at 4900° through two-stage. Culation at 1600° treceive approval in writing the control of the culation at 1600° treceive approval in writing the control of the culation at 1600° treceive approval in writing the culation at 1600° treceive app	ights, and lengths of proposed camportant proposed work) ing (1292°) and 176 journated with 100 sack i. Lige collar set at 220°	ints, 7", 23.00#, Just regular cement, 1	S: UU
I understand that this plan of work must	tive sands; show sizes, we ing points, and all other is 53°. 1.00°, N-80 Casi Lower stage certilsonite per sacids. Culation at 4900° through two-street. Culation at 1600° treceive approval in writing the control of the culation at 1600° treceive approval in writing the culation at 1600° treceive at	ights, and lengths of proposed camportant proposed work) ing (1292') and 176 journmented with 100 sack i. i	ints, 7", 23.00#, Just regular cement, 1	S: UU

Petroleum Engineer

Title