



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYLand Office Santa Fe  
Lease No. 080117  
Unit SW/4

## SUNDRY NOTICES AND REPORTS ON WELLS

|   |   |      |
|---|---|------|
| NOTICE OF INTENTION TO DRILL.....                   | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        | XXXX |
| NOTICE OF INTENTION TO CHANGE PLANS.....            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... | XXXX |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     | SUBSEQUENT REPORT OF ALTERING CASING.....       |      |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |      |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        | SUBSEQUENT REPORT OF ABANDONMENT.....           |      |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    | SUPPLEMENTARY WELL HISTORY.....                 |      |
| NOTICE OF INTENTION TO ABANDON WELL.....            |   |      |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 12, 1956, 19

## Huerfano Unit

Well No. 48-26 is located 1,380 ft. from IND line and 1,280 ft. from EX line of sec. 26

SW/4 Sec. 26

(1/4 Sec. and Sec. No.)

T 27-N R 9-W

(Twp.)

(Range)

N.M.P.M.

(Meridian)

N So. Blanco P.C.

(Field)

San Juan County

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 6381 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

April 27, 1956. After drilling to 2238' RKB (Top of Pictured Cliffs 2229') with rotary rig, set 55 joints 5-1/2" OD 15.5# J-55 casing at 2233' with 100 sacks cement. Moved off.

May 7, 1956. Moved in cable tools. Three hour test showed no water. After drilling to 2285', loaded 100 quarts solidified nitro-glycerin from 2244' to 2285' - tamped with 5' gravel and 50' calseal in casing. Unloaded hole May 9, 1956 at 6:30 P.M.

May 10, 1956. Sand oil treated from 2233' to 2285' with 17,700 gallons diesel oil and 27,500# sand. Flushed with 2,300 gallons diesel oil. Breakdown pressure 1400#. Injection 46.5 barrels per minute.

May 11, 1956. Ran 102 joints (2253') of 1" tubing - landed at 2253'. Shut well in for potential test, and to await pipe line connection.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company J. Glenn TurnerAddress Box 728Farmington, New MexicoBy C. Beeson Neal  
C. Beeson Neal, Agent in Farmington  
Title \_\_\_\_\_