

Initial Deliverability  
Test

NEW MEXICO OIL CONSERVATION COMMISSION  
GAS WELL TEST DATA SHEET - - SAN JUAN BASIN

(TO BE USED FOR FRUITLAND, PICTURED CLIFFS, MESAVERDE, & ALL DAKOTA  
EXCEPT BARKER DOME STORAGE AREA)

Pool BALLARD Formation PICTURED CLIFFS County SAN JUAN  
Purchasing Pipeline KL PASO NATURAL GAS COMPANY Date Test Filed 5-27-57  
Operator J. GLENN TURNER Lease MOHAWATO UNIT Well No. 48-26  
Unit L Sec. 26 Twp. 27n Rge. 9W Pay Zone: From 2228 To 2285  
Casing: OD 5-1/2" WT. 15.5# Set At 2233 Tubing: OD 1" WT. 1.7# T. Perf. 2243  
Produced Through: Casing X Tubing \_\_\_\_\_ Gas Gravity: Measured 0.655 Estimated \_\_\_\_\_  
Date of Flow Test: From 4-30-57 To 5-8-57 \* Date S.I.P. Measured 5-19-56  
Meter Run Size 4" Orifice Size 1.000 Type Chart Sq. Rt. Type Taps Flange

OBSERVED DATA

Flowing casing pressure (Dwt) \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (a)  
Flowing tubing pressure (Dwt) \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (b)  
Flowing meter pressure (Dwt) \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (c)  
Flowing meter pressure (meter reading when Dwt. measurement taken:  
Normal chart reading \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (d)  
Square root chart reading (\_\_\_\_\_) <sup>2</sup> x spring constant \_\_\_\_\_ = \_\_\_\_\_ psia (d)  
Meter error (c) - (d) or (d) - (c) \_\_\_\_\_ ± \_\_\_\_\_ = \_\_\_\_\_ psi (e)  
Friction loss, Flowing column to meter:  
(b) - (c) Flow through tubing: (a) - (c) Flow through casing \_\_\_\_\_ = \_\_\_\_\_ psi (f)  
Seven day average static meter pressure (from meter chart):  
Normal chart average reading \_\_\_\_\_ psig + 12 = \_\_\_\_\_ psia (g)  
Square root chart average reading (6.85) <sup>2</sup> x sp. const. 5 \_\_\_\_\_ = 235 psia (g)  
Corrected seven day avge. meter press. (p<sub>f</sub>) (g) + (e) \_\_\_\_\_ = 235 psia (h)  
P<sub>t</sub> = (h) + (f) \_\_\_\_\_ = 235 psia (i)  
Wellhead casing shut-in pressure (Dwt) 631 \_\_\_\_\_ psig + 12 = 643 psia (j)  
Wellhead tubing shut-in pressure (Dwt) 631 \_\_\_\_\_ psig + 12 = 643 psia (k)  
P<sub>c</sub> = (j) or (k) whichever well flowed through \_\_\_\_\_ = 643 psia (l)  
Flowing Temp. (Meter Run) 54 °F + 460 \_\_\_\_\_ = 514 °Abs (m)  
P<sub>d</sub> = 1/2 P<sub>c</sub> = 1/2 (l) \_\_\_\_\_ = 322 psia (n)

Q = \_\_\_\_\_ X  $\left( \frac{\text{FLOW RATE CALCULATION}}{\frac{V(c)}{V(d)}} \right)^* = \text{_____ MCF/day}$   
(integrated)

DELIVERABILITY CALCULATION

D = Q 194  $\left[ \frac{P_c^2 - P_d^2}{P_c^2 - P_w^2} \right]^n \frac{0.88}{1} = \text{_____ MCF/day}$   
309,700  
358,200

SUMMARY

P<sub>c</sub> = 643 psia  
Q = 194 Mcf/day  
P<sub>w</sub> = 235 psia  
P<sub>d</sub> = 322 psia  
D = 172 Mcf/day

Company J. GLENN TURNER  
By \_\_\_\_\_  
Title Engineer  
Witnessed by \_\_\_\_\_  
Company \_\_\_\_\_

- \* This is date of completion test.
- \* Meter error correction factor

REMARKS OR FRICTION CALCULATIONS

GL	(1-e <sup>-S</sup> )	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-S</sup> ) R <sup>2</sup>	P <sub>t</sub> <sup>2</sup> (Column i)	P <sub>t</sub> <sup>2</sup> + R <sup>2</sup>	P <sub>w</sub>
			Friction negligible			

