

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to surface. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER		RECEIVED APR 22 1969 OIL CON. COM. DIST. 3	5. LEASE DESIGNATION AND SERIAL NO. NM 012200
2. NAME OF OPERATOR El Paso Natural Gas Company			6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 990, Farmington, New Mexico - 87401			7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1840'S, 800'E			8. FARM OR LEASE NAME Dryden
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5817' GL		9. WELL NO. 5
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data			10. FIELD AND POOL, OR WILDCAT So. Blanco P. C.
NOTICE OF INTENTION TO:			11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 28, T-28-N, R-8-W N.M., P.M.
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☒	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	
(Other) ☐			(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*			

On 4-2-69 spudded well, drilled surface hole.

On 4-3-69 ran 4 joints 8 5/8", 24#, J-55 surface casing (134') set at ground level w/95 sacks of cement circulated to surface. W.O.C. 12 hours, held 600#/30 Min.

On 4-6-69 T.D. 2342', ran 75 joints 2 7/8", 6.4#, J-55 casing (2331') set at 2342' w/155 sacks of cement. W.O.C. until completion.

On 4-15-69 P.B.T.D. 2332', tested casing to 4000# O. K. Perf. Pictured Cliffs 2224-29', 2236-48' w/20 SPZ. Frac w/28,000# 10/20 sand and 28,000 gal. water. Max. pr. 4000#, BDP 1600#, avg. tr. pr. 3100#, I.R. 20 BPM. Dropped 1 set of 20 balls, flushed w/550 gal. water. ISIP 750#, 5 Min. 700#, 15 Min. 650#.

RECEIVED

APR 21 1969

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED Original signed by Carl E. Matthews TITLE Petroleum Engineer DATE 4-21-69

(This space for Federal or State office use)

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

