Form	9-331		
(May	1963		

UNITED STATES SUBMIT IN TRIPLICATE* DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

-				_			
G	F	7	$^{\circ}$	LOGI	CAL	SURVEY	

GEOLOGICAL SURVEY	NM 03380 /		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
1.	7. UNIT AGREEMENT NAME		
OIL GAS WELL X OTHER 2. NAME OF OPERATOR	S. FARM OR LEASE NAME		
El Paso Natural Gas Company	Florance D		
3. ADDRESS OF OPERATOR NVM 97401	9. WELL NO. 17		
PO Box 990, Farmington, NM 87401 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*	10. FIELD AND POOL, OR WILDCAT		
See also space 17 below.) At surface 1190'S, 890'E	Undes. Chacra 11. sec., T., E., M., OR BLE. AND SURVEY OF AREA Sec. 17, T-27-N, R-8-W NMPM		
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6734'GL	San Juan New Mexico		
16. Check Appropriate Box To Indicate Nature of Notice, Report, or			
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT SHOOT OR ACIDIZE ABANDON* CHANGE PLANS (Other) (Note: Report result	REPAIRING WELL X ALTERING CASING ABANDONMENT* Alts of multiple completion on Well expletion Report and Log form.) ex, including estimated date of starting any ical depths for all markers and zonea perti-		
 7-5-72 T. D. 3884'. Ran 125 joints 2 7/8", 6.4#, J-55 product 3884'. Baffle set at 3873'. Cemented with 668 cu.ft. of Top of cement at 1850'. PBTD 3873'. Perf'd 3820-3836' with 32 shots per zone. 20/40 sand and 24,865 gallons treated water. No balls 	rement. WOC 18 hours. Frac'd with 24,000#		
970 gallons.			
18. I hereby certify that the forgaing is true and correct SIGNED Petroleum Engineer	DATE July 27, 1972		
(This space for Federal or State office use)			
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE		