

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

USNM - 12020

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL  GAS WELL  OTHER

2. NAME OF OPERATOR  
Kirby Exploration Company

3. ADDRESS OF OPERATOR  
P. O. Box 1745, Houston, Texas 77001

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

990' FEL & 990' FSL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Kirby - Gallegos

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Gallegos Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, T27N, R13W

12. COUNTY OR PARISH

San Juan

New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

5994 K.B.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF   
FRACTURE TREAT   
SHOOT OR ACIDIZE   
REPAIR WELL

PULL OR ALTER CASING   
MULTIPLE COMPLETE   
ABANDON\*   
CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF   
FRACTURE TREATMENT   
SHOOTING OR ACIDIZING   
(Other)

REPAIRING WELL   
ALTERING CASING   
ABANDONMENT\*

Application for permit to Drill.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-26-75 - Move in rotary rig - Four Corners Drilling Company.  
Spud at 5:00 p.m., 8-26-75: Drill 12-1/4" hole to 238 ft.  
Set 8-5/8" 24.0 # K-55 ST & C casing at 234 ft. Cement casing with 150 sacks Class "A" + 2% CaCl2. Cement circulated.  
Plug down at 11:15 p.m., 8-26-75. WOC 12 hrs. Pressure BOP's to 500 psi for 30 minutes.

RECEIVED

AUG 28 1975

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED Jack D. Cook

TITLE Agent

DATE 8-28-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: