

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N00-C-4-20-2976

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT

8. FARM OR LEASE NAME

Barbara Kay

9. WELL NO. NOV 1 1975
3

10. FIELD AND FOOT, OR WILDCAT
Wildcat DIST 3

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Sec. 19, T27N, R19W

12. COUNTY OR PARISH 13. STATE
San Juan N.M.

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Northwest Pipeline Corporation

3. ADDRESS OF OPERATOR

P.O. Box 90 Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

990' FNL & 2225' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5762' GR

10.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

"Spud & Intermediate Casing"

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-19-75

MOL & RU. Spud at 3:45 PM. Drilled 12 1/4" hole to 160'.
Went in hole and reamed 17 1/4" hole to 156'. Ran 4 joints
(156') 13 3/8", 48#, H-40 casing set at 156' KB.

10-20-75

Cemented w/140 sxs Cl. "B" w/1/4# flocele per sx & 3% CC.
Good circ. Tested casing to 600 PSI for 1/2 hr. Held OK.

10-21-75

Drilled 12 1/4" hole to 1379' KB.

10-22-75

Ran 35 joints (1366') 8 5/8", 24#, J-55 casing set @ 1379' KB.
Cemented w/525 sxs Howco light cement w/10# Gilsonite per sx,
followed w/100 sxs Cl. "B" w/2% CC. Cement. Circ.

RECEIVED

OCT 31 1975

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

D. H. Maroncelli
D. H. Maroncelli

TITLE

Petroleum Engineer

DATE

10-29-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY;