UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

D. LEASE			
USA NM 035	49 USA	SF 0	80112 ,
6. IF INDIAN,			,

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME	
	Gooch	
1. oil gas (XX) well well other	9. WELL NO.	
2. NAME OF OPERATOR	2	
Tenneco Oil Company	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Basin Dakota	
720 S. Colorado Blvd., Denver, CO 80222	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec 29, T28N, R8W	
AT SURFACE: 1850'FNL, 2510'FEL, Unit G	12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL:	San Juan New Mexico	
AT TOTAL DEPTH:	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
	5887 'GL	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF FRACTURE TREAT		
SHOOT OR ACIDIZE	1.2	
acara meri	(NOTE: Report results of multiple completion or zone	
PULL OR ALTER CASING	Change on Form 9–330.)	
MULTIPLE COMPLETE CHANGE ZONES U.S. CEO.		
ARANDON*	109L SURING 1	
(other) spud, surface & production csg	N. M. of	
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertined 9/10/79-9/13/79 	lirectionally drilled, give subsurface locations and	
Spudded 13 3/3" hole on 9/10/79 and drilled to 36#, K-55 csg and set @ 217'. Cemented w/200 S CACL2. Circulated to surface. WOC 12 hrs. NUBO to 1000 PSI for 30 min held ok. Reduced hol to 3100'. Ran 74 jts. 7" 23#, K-55 csg and set chemical wash. 575 Sx 50/50 Pozmix, 4% gel, 6 Tailed in w/150Sxctass B neat cement, 2% CACL2 Reduced hole to 6 1/4" and continued drilling.	x class B cement, w/2% P. Pressure tested csg e to 8 3/4" and drilled 0 3100'. Cemented w/20 BBL 1/4# Sx Gilsonite 0 0600 be and .06% 9-60. Voc 12 hrs.	
Subsurface Safety Valve: Manu. and Type	set @ Condition	
18. Thereby certify that the foregoing is true and correct	avison	
SIGNED TITLE Admin. Super	VISUI DATE	
(This space for Federal or State of		
APPROVED BY TITLE TITLE	DATE	

Myroca