

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-33016

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

STP-FEDERAL

9. WELL NO.

#1-17

10. FIELD AND POOL, OR WILDCAT

Greenhorn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

NE NW Sec. 17, T27N-R12W

12. COUNTY OR PARISH 13. STATE

San Juan

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR
Patrick Petroleum Corp. of Michigan

3. ADDRESS OF OPERATOR
388 Denver Club Building, Denver, Colorado 80202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
2375' FWL and 790' FNL

14. PERMIT NO.

None

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5739' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) plug back

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)


REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set cast iron bridge plug at 5840'. Dumped 5 sx of cement on top of plug. P.B.T.D. at 5775'. Perforated the Greenhorn formation at 5688'- 5694' w/2 spf. At 5720'- 5734' w/2 spf and at 5748'-5758' w/2 spf. Acidized w/200 gals. mud acid w/claymaster and non-emulsifying agent.



18. I hereby certify that the foregoing is true and correct

SIGNED

Clay S. Chodera

TITLE

LeCLAIR-WESTWOOD, INC. - Agent

Production Engineer

DATE

12/14/79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOC

*See Instructions on Reverse Side