## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

|     | 5.  | LE <b>AS</b> E<br>SF 080112  |
|-----|-----|--|
|     | 6.  | IF INDIAN, ALLOTTEE OR TRIBE NAME  |
| ent | 7.  | UNIT AGREEMENT NAME  |
|     | 8.  | FARM OR LEASE NAME<br>Riddle F   |
|     |     | WELL NO.<br>3A   |
|     | 10. | FIELD OR WILDCAT NAME<br>Blanco Mesa Verde   |
| .7  | 11. | SEC., T., R., M., OR BLK. AND SURVEY OR<br>AREA Sec. 20, T-28-N, R-8-W<br>N.M.P.M. |
|     | 12. | COUNTY OR PARISH 13. STATE New Mexico  |
| Ε,  | 14. | API NO.  |

| SUNDRY NOTICES AND REPO   |  | NAME   |
|---|--|--|
| Do not use this form for proposals to drill or to deep reservoir. Use Form 9-331-C for such proposals.)   | n or plug back to a different  8. FARM OR LEASE N Riddle F   | IAME   |
| 1. oil gas y other  | 9. WELL NO.<br>3A  |  |
| 2. NAME OF OPERATOR El Paso Natural Gas Compa   |  |  |
| 3. ADDRESS OF OPERATOR Box 289, Farmington, New 4. LOCATION OF WELL (REPORT LOCATION  | Mexico 11. SEC., T., R., M., O AREA Sec. 20  | R BLK. AND SURVEY OR<br>, T-28-N, R-8-W            |
| below.) AT SURFACE: 1825'N, 1625' AT TOP PROD. INTERVAL:  | N.M.P.J  12. COUNTY OR PARIS  San Juan   |  |
| AT TOTAL DEPTH:   | 14. API NO.  |  |
| 16. CHECK APPROPRIATE BOX TO INDICAT REPORT, OR OTHER DATA  | · · · · · · · · · · · · · · · · · · ·  | OW DF, KDB, AND WD)                                |
| REQUEST FOR APPROVAL TO: SUBSE TEST WATER SHUT-OFF  FRACTURE TREAT  SHOOT OR ACIDIZE  REPAIR WELL  PULL OR ALTER CASING  MULTIPLE COMPLETE  CHANGE ZONES  ABANDON*  (other) | QUENT REPORT OF:    X  | f multiple completion or zone<br>n 9–330.)         |
| 17. DESCRIBE PROPOSED OR COMPLETED of including estimated date of starting any measured and true vertical depths for all r  | PERATIONS (Clearly state all pertinent details, a roposed work. If well is directionally drilled, give narkers and zones pertinent to this work.)* | and give pertinent dates, subsurface locations and |
| at 2451'. Cemented  | ints 7", 20#, K-55 intermediate oww/304 cu. ft. cement. WOC 12 houent at 1200'.  | asing 2440' set<br>ers;held 1200#/30               |
| 2288-4810'. Float o   | ints 4 1/2", 10.5#, K-55 casing 1<br>ollar set at 4792'. Cemented w/43   | liner 2522' Set<br>37 cu. ft. cement.              |
| WOC 18 hours.   |  |  |
|   |  | er.  |
| Subsurface Safety Valve: Manu. and Type   |  | Set @Ff.   |
| 18. I hereby certify that the foregoing is true a   |  | ary 3, 1979  |
| (Thi  | space for Federal or State office use)   |  |
| APPROVED BY   | DATE   |  |
|   | こっせしば  |  |

\*See Instructions on Reverse Side