

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1760'S, 1725'E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF 077951

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Frost

9. WELL NO.
3R

10. FIELD OR WILDCAT NAME
Fulcher Kutz Pic. Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 26, T-27-N, R-10-W
NMPM

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DE, KDB, AND WD)
6669' GL

RECEIVED

NOTE: Report results of multiple completion or zone change on Form 9-330.)

JAN 19 1980
OIL CON. COM.
DIST.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 12-9-80: Spudded well. Drilled surface hole. Ran 3 joints 8 5/8", 24#, K-55 surface casing 114' set at 126'. Cemented w/106 cu. ft. cement. Circ. to surface. WOC 12 hours; held 600#/30 minutes.
- 12-13-80: TD 2647'. Ran 98 joints 2 7/8", 6.4#, J-55 production casing 2637' set at 2647'. Baffle set at 2637'. Cemented w/ 386 cu. ft. cement. WOC 18 hours. Top of cement at 1300'.
- 12-23-80: PBTD 2637'. Tested casing to 4000#, OK. Perfed: 2419, 2423, 2427, 2430, 2434, 2437, 2473, 2476' w/1 SPZ. Fraced w/ 25,000# 10/20 sand, 30,000 gal. wtr. Flushed w/500 gal. wtr.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. B. Buico TITLE Drilling Clerk DATE December 17, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

BW