

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 03603A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hammond

9. WELL NO.

8

10. FIELD AND POOL, OR WILDCAT

So. Blanco PC

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

SE 1/4 25-27N-8W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

1.

OIL ☐ GAS ☒ OTHER ☐  
WELL WELL

2. NAME OF OPERATOR

Western Oil & Minerals, Ltd.

3. ADDRESS OF OPERATOR

P. O. Drawer 1228, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

820' FEL & 1845' FSL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5989' UGL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☒ csg. report

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4-11-80 Ran 3 jts. 8-5/8" OD 24# new K-55 csg & Halliburton guide shoe & insert float, 1st jt. w/2 centralizers. Set 1.5' below GL, landed 132' KB. Cmt by Halliburton w/120 sxs reg. class B 2% CaCl<sub>2</sub>. Displaced w/5.25 bbls. Start wtr ahead break circ. P.D., displ. w/5.2 bbls. WOC 7:15 a.m. Cmt fell, fill annulus thru 1".

4-16-80 Ran 55 jts. 4-1/2" OD 10.5# new K-55 csg at 2310' KB. Cmt by Halliburton w/600 sxs 50/50 pos mix 6 1/4#/sx gilsonite in 2 stages. Good circ. throughout. Well bridged off. Left 1500' cement in csg. on 2nd stage.

4-28-80 W0 completion rig.

ACCEPTED FOR RECORD

APR 28 1980

RECEIVED  
FARMINGTON  
BY *[Signature]*  
APR 28 1980  
OIL CON. COM.  
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

*[Signature]*  
Elliott A. Riggs

TITLE Agent

DATE April 28, 1980

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side