

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
720 S. Colorado Blvd., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 980' FNL 905' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Spudding/csg. report

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF - 078390

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Price

9. WELL NO.
#4

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 14 T28N R8W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6293 gl.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
9/2/80

Spudded 12 1/4" hole 9/1/80. Drilled to 295'. Circ. TOH. Ran 7 jts 9 5/8" csg. set @ 292'. Cmt. w/230 sx CL-B w/2% CACL 2. Circ. cmt. to surface. Reduce hole to 8 3/4". Ran 86 jts. (3609') 7" 23# csg. Set csg. @ 3600'. Cmt. w/550 sx Howco Tite, 6% gel. Tail in w/150 sx CL-B & 2% CACL 2. Circ. cmt to surface NU BOP. Test to 600 PSI. Reduce hole to 6 1/4", Ran 16 jts. 4 1/2" 11.5# & 83 jts 10.5# liner, hit bridge @ 7330. Pick up DP & TIH to 5457'. Circ. hole @ TOF. Cmt. w/38 sx 65/35 Tite, Est. TOP @ 5154'. Pull DP to 4400' Cmt w/33 sx 65/35 Tite. est. TOP @ 4344. Pull DP to 3811'. Spot 60 sx CL-B w/2% CACL 2. Pull DP to 3190'. Circ. Top of plug, Tag TOC @ 3575'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carly Hutton TITLE Asst. Div. Admin. Mgr. DATE September 29, 1980

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY 1080
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

FARMINGTON DISTRICT

BY BV

NMOCC