

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR

DEPCO, Inc.

3. ADDRESS OF OPERATOR

1000 Petroleum Building-Denver, CO 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 850' FSL, 850' FEL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Supplementary Report ☐

5. LEASE

SF-078895

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

--

7. UNIT AGREEMENT NAME

--

8. FARM OR LEASE NAME

Mudge "A"

9. WELL NO.

11

10. FIELD OR WILDCAT NAME

West Kutz P.C.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 18-T27N-R11W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

30-045-24268

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6174' GR; 6186' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 8:00 PM 5-7-80. Drilled 12 1/4" hole to 138' KB. Ran 3 jts 8-5/8" 24# K55 casing, landed @ 137' KB. Cement casing w/100 sx Regular containing 3% CaCl₂. Circulate cement to surface. WOC 12 hrs. Drilled to 2030' TD. Ran DIL w/linear correlation log. Ran 4 1/2" - 10.5# - K55 casing, landed @ 2030' KB. Cemented casing w/250 sx 50/50 pozmix containing 6% gel, 1/4#/sx flocele, 6 1/4#/sx gilsonite, followed by 75 sx Regular Class "B". Rig released 5:30 PM 5-10-80.

Subsurface Safety Valve: Manu. and Type None Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. F. Schwenn Prod. Supt. DATE 5/13/80

W. F. Schwenn

(This space for Federal or State office use)

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 16 1980

FARMINGTON DISTRICT

BY

NMOCCT