

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
DEPCO, Inc.
3. ADDRESS OF OPERATOR
1000 Petroleum Bldg - Denver, CO 80202
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1820' FWL, 1520' FSL (NE/4 SW/4)
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐

(other) Subsequent Report of Operations

5. LEASE
NM-0359211
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
--
7. UNIT AGREEMENT NAME
--
8. FARM OR LEASE NAME
Federal 30
9. WELL NO.
23
10. FIELD OR WILDCAT NAME
West Kutz, P.C.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 30-T27N-R11W
12. COUNTY OR PARISH 13. STATE
San Juan NM
14. API NO.
30-045-24813
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6137' GR 6149' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 2 PM 4-1-81. Drilled 12 1/4" hole to 154' KB. Ran 3 jts - 135.59' - 8-5/8" - 24# - K55 - R3 - ST&C casing landed @ 148' KB. Cemented w/100 sx Class "B" regular containing 3% CaCl₂ & 1 sx Flocele. Cement circulated to surface. PD 5:30 PM 4-1-81. WOC 12 hrs.

Drilled 7-7/8" hole to 1875' TD. Ran DIL & CNL/FDC w/GR logs. Ran 45 jts - 1844.37' 4 1/2" - 10.5# - J55 - R3 - ST&C casing landed @ 1856' KB. Cemented w/265 sx 65/35 poz-mix, 12% gel, 12 1/4# Gilsonite/sx, followed by 100 sx Class "B" regular cement. Cement circulated to surface. PD 10:45 PM. Rig released 11:30 PM 4-3-81. WOC.

Subsurface Safety Valve: Make and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Wm. S. Schwert Prod. Supt.-So. Rks DATE 4/6/81

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE

MOCC

*See Instructions on Reverse Side