

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

DEPCO, Inc.

3. ADDRESS OF OPERATOR

1000 Petroleum Bldg - Denver, CO 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FNL, 1650' FWL (NE $\frac{1}{4}$ -NW $\frac{1}{4}$)

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) Subsequent Report of Operations

5. LEASE

N. M. 03523

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 31

9. WELL NO.

21

10. FIELD OR WILDCAT NAME

West Kutz P.C.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 31-T27N-R11W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

14. API NO.

30-045-24964

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6073' GR 6085' KB

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 1 PM 4-23-81. Drilled 12 $\frac{1}{4}$ " hole to 135' KB. Ran 3 jts - 120.62' 8-5/8" - 24# - K55 - R3 - ST&C casing landed @ 135' KB. Cmt'd w/100 sx Class "B" regular containing 3% CaCl₂ & 1 sx Flocele. Cmt circulated to surface. PD 5 PM 4-23-81. WOC 12 hrs. Drld 7-7/8" hole to 1775' TD. Ran DIL & CNL/FDC w/GR & Caliper logs. Ran 43 jts - 1758.38' - 4 $\frac{1}{2}$ " - 10.5# J55 - R3 - ST&C casing landed @ 1770' KB. Cmt'd w/235 sx 65/35 Pozmix, 12% gel, 12 $\frac{1}{2}$ # gilsonite/sx followed by 100 sx Class "B" regular. Cement circ'd to surface. PD 3:45 PM. Rig released 4:30 PM. WOC.

ACCEPTED FOR RECORD

MAY 01 1981

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.
FARMINGTON DISTRICT

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

Prod. Supt.

So. _____

DATE

4/27/81

Rockies

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
AS AMENDED

MAY 01 1981

JAMES F. SIMS
DISTRICT ENGINEER

*See Instructions on Reverse Side

NMCCO