

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other
2. NAME OF OPERATOR
DEPCO, Inc.
3. ADDRESS OF OPERATOR
1000 Petroleum Bldg - Denver, CO 80202
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1090' FSL, 960' FEL (SE/4 SE/4)
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
- TEST WATER SHUT-OFF ☐ ☐
- FRACTURE TREAT ☐ ☐
- SHOOT OR ACIDIZE ☐ ☐
- REPAIR WELL ☐ ☐
- PULL OR ALTER CASING ☐ ☐
- MULTIPLE COMPLETE ☐ ☐
- CHANGE ZONES ☐ ☐
- ABANDON* ☐ ☐
- (other) Subsequent Report of Operations

5. LEASE
SF078896
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal 33
9. WELL NO.
44
10. FIELD OR WILDCAT NAME
West Kutz P.C.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 33-T27N-R11W
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
30-045-24967
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6262' GR 6274' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 7 PM 5-8-81. Drld 12 1/2" hole to 135' KB. Ran 3 jts - 120.10' - 8-5/8" 24# - K55 - R3 ST&C casing landed @ 132' KB. Cmt'd w/100 sx Cl "B" regular cmt containing 3% CaCl₂ & one sx flocele. Cmt circ'd to surface. PD 11 PM 5-8-81. WOC 12 hrs.

Drld 7-7/8" hole to 1982' TD. Ran DIL & CNL/FDC w/GR & Caliper logs. Ran 48 jts - 1970.48' - 4 1/2" - 10.5# - J55 - R3 - ST&C casing landed @ 1982' KB. Cmt'd w/235 sx 65/35 Pozmix, 12% gel, 12 1/2# gilsonite/sx followed by 100 sx Class "B" regular cmt. Good rtns thru out. Cmt circ'd to surface. PD 8:15 AM. Rig released 9 AM 5-11-81. WOC.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. S. Schwenm TITLE Prod. Supt. - So. DATE May 12, 1981
Rockies

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

MAY 15 1981

FARMINGTON DISTRICT

BY W. S. Schwenm