

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
DEPCO, Inc.
3. ADDRESS OF OPERATOR
1000 Petroleum Bldg - Denver, CO 80202
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FNL, 990' FWL (NW/4 NW/4)
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

(other) Subsequent Report of Operations

5. LEASE
NMO359211
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
--
7. UNIT AGREEMENT NAME
--
8. FARM OR LEASE NAME
Federal 30
9. WELL NO.
11
10. FIELD OR WILDCAT NAME
West Kutz P.C.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 30-T27N-R11W
12. COUNTY OR PARISH 13. STATE
San Juan New Mexico
14. API NO.
30-045-24997
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6109' GR 6121' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 7 PM 5-11-81. Drld 12 1/4" hole to 137' KB. Ran 3 jts - 116.92' - 8-5/8" 24# - K55 - R3 - ST&C casing landed @ 129' KB. Cmt'd w/100 sx Class "B" regular cmt containing 3% CaCl₂ & one sx flocele. Cmt circulated to surface. PD 11:30 PM 5-11-81. WOC 12 hrs.

Drilled 7-7/8" hole to 1875' TD. Ran DIL and CNL/FDC w/GR & caliper logs. Ran 45 jts - 1841.00' - 4 1/2" - 10.5# - J55 - R3 - ST&C casing landed @ 1853' KB. Cmt'd w/230 sx 65/35 Pozmix, 12% gel, 12 1/4# gilsonite/sx followed by 100 sx Class "B" regular cmt. Cmt circulated to surface. PD 10:30 PM. Rig released 11 PM 5-13-81. WOC.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John P. Schwenk TITLE Prod. Supt. - So. DATE May 14, 1981
Rockies

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side