

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Energy Reserves Group, Inc.
3. ADDRESS OF OPERATOR
P.O. Box 3280 - Casper, Wyoming 82602
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1,670' FSL & 1,100' FEL (NE/SE)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Well History	<input type="checkbox"/>	<input checked="" type="checkbox"/>

5. LEASE SF-078019
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME E.H. Pipkin
9. WELL NO. 16
10. FIELD OR WILDCAT NAME Kutz Fruitland/Fulcher Kutz PC
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA Sec. 1-T27N-R11W
12. COUNTY OR PARISH San Juan
13. STATE New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) G.L. 5,732'; K.B. 5,737'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above referenced well was spudded @ 10:00 AM 9-29-81.

Drld 9-7/8" hole to 107'. Ran 3 jts 7" O.D., 23#, K-55, R-3, ST&C, new casing set @ 107'. Cemented w/105 sx of Class "B" cement w/2% CaCl₂ & 1/4# Flocele/sx.

Drld 6-1/4" hole to 1,725' & ran logs.

Ran 42 jts 4-1/2" O.D., 10.5#, K-55, R-2, ST&C, new casing set @ 1,715' (KB). Cemented w/400 sx of 50-50 Pozmix w/2% Gel; 0.5% CFR-2 & 1/4# Flocele/sx. Plug down @ 8:30 AM 10-5-81. Good cement returns.

W.O.C.T.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth C. Gillespie TITLE Drlg Supt - RMD DATE 10-5-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: