ξ

1973	Form Approved. Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE 0 5 00 00 00 00 00 00 00 00 00 00 00 00
DEPARTMENT OF THE INTERIOR	SF-078019 [경험경 등 변화]
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	THE PART OF THE PA
1 oil go	8. FARM OR LEASE NAME
well well other	E. H. Pipkin 4
2. NAME OF OPERATOR Energy Reserves Group, Inc.	17 ब्रह्मिस इ. के उन्हें
3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Kutz Fruitland
P.O. Box 3280, Casper, Wy. 82602	West Kutz Pictured Cliffs  11. SEC., T., R., M., OR BLK. AND SURVEY OR
<ol> <li>LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)</li> </ol>	AREA Sec. 1, T27N-R11W
AT SURFACE: 1,600'FSL & 890'FWL (NW/SW)	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan En New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO. 46.000 TO 30.000
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	GL-5,960'; KB-5,964'
TEST WATER SHUT-OFF  FRACTURE TREAT	5 4 2 8
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Parent Control of the Control
PULL OR ALTER CASING	(NOTE: Report results of multiple completion of zone change on Form 9–30.)
MULTIPLE COMPLETE	OC 15 1981
ABANDON*	PERSONAL PROPERTY OF THE PROPE
(other) Well History	COM.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (CLASSICAL)	3.72
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent	all pertinent details, and give pertinent dates, rectionally drilled, give subsurface locations and
The above referenced well was spudded at 10:0	
Drilled 9-7/8" hole to 122'.	1
Ran 3 jts 7" o.d., 23#, K-55, R-3, S.T.&C.	new casing section + 3001
w/oo sx. or class B dement w/2% CaCl <sub>2</sub> & 1/4#	Flocele/sx. Plug down at 3:00 P.M.
9-27-31. Good cement returns	The state of the s
Drilled 6-1/4" hole to 1,950' and ran logs.	Ran 50 jts. 3 4 4 1 / 2" b.d., 10.5#,
K-55, R-3, S.T.&C. New casing set at 1,940'. w/2% gel; 0.5% CFR-2 & 1/4# Flocele/sx. Plug of	Cemented w/400 sv of 50-50 hozmin
W.O.C.T.	
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
	o ich ber stod ost stod ost stode om vode om tomber odomber dennes denne
Subsurface Safety Valve: Manu. and Type	Since Set @ Ft.
18. I hereby gertify that the foregoing is true and correct	
SIGNED A 2200 C. Milleger TITLE Drilling Sup't.	- RMD 10-7-81 29 3771
(This space for Federal or Control	
APPROVED BY	The state of the s
CONDITIONS OF APPROVAL, IF ANY:	DATE TOTAL TRESPRES
	DATE THE BRIDGE AND T
	<b>日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日</b>

NMOCC

FARMINGTUN DUTE IT BY -