

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐

2. NAME OF OPERATOR

CURTIS J. LITTLE

3. ADDRESS OF OPERATOR

P. O. Box 2487
Farmington NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 790'FNL & 815'FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE

SF-081087

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

WIEDEMER

9. WELL NO.

#2

10. FIELD OR WILDCAT NAME

Fulcher Kutz PC

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec.34-27N-10W

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

14. API NO.

30-045-25397

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6692'GL

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☒

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐


PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-24-82 SPUD 5:00 pm. Drld 130' 9-7/8" hole. Ran 122' 7" 23# csg. Set at 122'GL. Cmt w/65 sx cmt w/2% CaCl & 1/4# Flocele/sack (76.6 cu.ft.slurry). Circ. 3.54 cu.ft. cmt to surf. Plug down 10:00 pm 8-24-82.

8-28-82 REACHED T.D. 2562'. Ran logs. Ran 85 jts 2-7/8" 6.5# csg. Set @ 2559'GL. PBTD 2544'GL. Cmt. with 450 sx 50/50 poz mix with 2% gel & 6-1/4# gilsonite per sack. Followed w/100 sx Class B neat (743.5 cu.ft.slurry). PD 6:11 am 8-29-82. Circ. 50 sx (70 cu.ft.) cement to surface. Pressure tested to 3500#. Held OK.

Subsurface Safety Valve: Manu. and Type n/a Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Roy Lee Pritchard TITLE Agent DATE 9-8-82

(This space for Federal or State office use)

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 10 1982

*See Instructions on Reverse Side

NMOCC

BY Smm

