

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P.O. Drawer 570, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 790' FNL & 1750' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Cement & Casing Report ☒

5. LEASE

NM - 33026

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Trading Post

9. WELL NO.

#1

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 34, T27N, R12W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5846' GL

(NOTE: Report results of multiple completions or zones change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3-3-83 Drilled 7-7/8" hole to a total depth of 6000'. Ran 149 joints (5987') of 4-1/2", 10.5#, K55 casing set at 5999'. Cemented first stage with 303 cubic feet of Class "B" containing 50/50 POZ, 6% gel, 1/4# celloflake. Tail in with 59 cubic feet of Class "B" containing 2% CaCL2. Plug down at 11:00 am, on 3-3-83. Cemented 2nd stage with 818 cubic feet Class "B" containing 50/50 POZ, 6% gel, 1/4# celloflake, 2% CaCL2. Tail in with 59 cubic feet of Class "B" containing 2% CaCL2. Plug down at 4:00 pm on 3-3-83. Cemented 3rd stage with 383 cubic feet Class "B" containing 50/50 POZ, 6% gel, 1/4# celloflake & 2% CaCL2. Tail in with 59 cubic feet Class "B" containing 2% CaCL2. Plug down at 8:00 pm on 3-3-83. Top of cement at 450' by Temperature Survey.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Sherry Stanley TITLE Secretary DATE March 14, 1983

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE ACCEPTED FOR RECORD

\*See Instructions on Reverse Side

NMCCC

MAR 28 1983

FARMINGTON DISTRICT

BY 4/8