

Schlosser WN Federal #1R
Proposed Wellbore Configuration

TD: 6830' PBD: 6748' RKB: 14'
 Completed 1/85

9 5/8", 36#, K-55, STC Csg set
 at 505' w/300 sx. Circ cmt to surf.

- A. 2-3/8" shear out plug
 - B. 1 jt 2-3/8" prod tbg
 - C. 1.81" "P" Nipple
 - D. ±560' 2-3/8", 4.7, J-55, 8rd tbg w/turned down & beveled couplings
 - E. Model AL-5 dual hydrostatic pkr.
 - F. ±6000' 2-3/8", 4.7#, J-55, 8rd tbg w/turned down & beveled couplings
- Set dual pkr @ ±6000'. 8cm long string @ ±6600'.

- A. Model "K" parallel anchor w/straight pull release
- B. Perforated nipple
- C. 2-3/8" seating nipple
- D. ±5970' 2-3/8", 4.7#, J-55 8rd tbg w/turned down & beveled couplings.

DV Tool at 4811'

Proposed Gallup Perfs: 5858, 60, 62, 64,
 66, 68, 70, 72, 74, 76, 78, 80, 82, 84, 86,
 88, 90, 92, 94, 96, 98, 9900, 02, 04, 06,
 08, 10, 20, 22, 24, 26, 28, 30, 32, 34, 36,
 38, 40, 42, 44, 46, 48, 50, 62, 63, 64, 65,
 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76,
 77, 78, 79 & 80 (62 Holes)

AL-5 @ 6000'

Dakota Perfs: 6615'-62'
 (2SPF-96 Holes)

LS blind @ ±6600'

7", 29#, S-95, LTC Csg set at
 6829': Cmt'd 1st stage w/475sx(Circ)
 Cmt'd 2nd stage w/1050sx(Circ)

