

Form 3160-5  
(June 1990)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

NOO-C-14-20-7467

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

890' FSL - 890' FWL  
Sec. 22, T27N, R13W, NMPM

CA, Agreement Designation

3. Name and No.

Lucky Billy Charlie 2

API No.

90-045-26454

Field and Pool, or Exploratory Area

Gallegos Gallup Ext.

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## TYPE OF SUBMISSION

☒ Notice of Intent☐ Subsequent Report☐ Final Abandonment Notice

## TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plan to plug and abandon as follows:

1. Set cast iron bridge plug 50' below Gallup top (4605')
2. Spot 100' Class B cement plug on top of cibp from 4655' - 4555'.
3. Spot 100' cement plug across Mesaverde top (2143') from 2193' - 2093' inside casing.
4. Spot 100' cement plug across Pictured Cliffs top (1323') from 1373' - 1273' inside casing.
5. Spot 100' cement plug across surface casing shoe (195') from 245' - 145' inside casing.
6. Spot 50' surface plug.
7. Pump down 8-5/8" x 4-1/2" casing annulus. If able to pump into annulus, cement with adequate volume to fill annulus to 50' below surface casing shoe.
8. Set dry hole marker.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander Title Vice-president

Date 6/17/99

(This space for Federal or State office use)

Approved by

/s/ Duane W. Spencer

Title

Team Lead, Petroleum Management

Date

JUN 22 1999

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

\*See Instruction on Reverse Side