

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ Helium other

2. NAME OF OPERATOR

S.E.R.H., Inc.

3. ADDRESS OF OPERATOR

P. O. Box 312, Otis, Kansas 67565

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)

AT SURFACE: 790' FNL; 990' FWL NW/4 NW/4 Sec. 32
AT TOP PROD. INTERVAL: Unit D
AT TOTAL DEPTH

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Spud Well ☒

SUBSEQUENT REPORT ON:

☒

☐

☐

☐

☒

5. LEASE

N00-0-14-20-4158

6. IF INDIAN, ALI OTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo 32

9. WELL NO.

3-32

10. FIELD OR WILDCAT NAME

Beautiful Mountain

11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA 32-27N-19W

NMP

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5856' Gr; 5869' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
AUG 12 1985
OIL CON. DIV. 1
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud well by Young Rig #4 - 8:45 pm, 8/2/85. Drill 17 1/2" hole to 78'. Ran 2 jts. 13-3/8" 68# Egs. 3 Cl. A SS Casing Tally 77.20' Set @ 77'. Cement by WOODCO w/130 sx (153 cft.) Cl. "B" 2% CaCl. Displace to 62' complete @ 3:45 am, 8/3/83. Cement circ. - surplus 9 bbls. 60 sx. WOC-12 hrs. Nipple up conductor. Drill 12-1/4" hole w/spud mud to 1500'. Ran 35 jts. 8-5/8" 24# J Rg. 3; Cl. A; casing. Tally 1478.72' w/GS 1.20'. Total tally 1479.92 and set @ 1493' & I.F. up 1 jt. at 1451' - 3 centralizers. Cement by HOWCO w/890 sx. (1050 cft.) Cl. "B"; 2% CaCl & 1/8#/sx. Floccid. Pump plug to 145'. Cement circ. w/298 sx. excess. Check float - OK. Comp. @ 4:00 am, 8/5/85. WOC-15 hrs. Nippled up, Test Blowout Preventers & Bleed-off Manifold to 860 psi; 30 min. - OK. Drill out w/7-7/8" bit. 8/6/85 @ 6:00 am, Drilg. 2 1995'.

Would like to change well designation to Navajo 32 Well No. 3 to correspond with computer printouts.

Subsurface Safety Valve: Manuf. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

John M. Heller

Field Agent

DATE 8/7/85

P. O. Box 1507, Durango, Colorado 81302

(This space for Federal or State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

See instructions on Reverse Side

AUG 12 1985

NMCCG

FARMINGTON RESOURCE AREA

BY